





# Ultra-Economy Exit Sign Combo













FCC

Ro

PROJECT:

DATE:

TYPE:

PREPARED BY:







### **KEY FEATURES**

- Universal faces with red or green letters
- Durable thermoplastic design
- Remote head capable, see Remote Head Compatibility List
- Options with **90 minutes** of emergency illumination
- Select models compliant with California Title 20

\*Select models

# **PERFORMANCE**

Catalog Number	# of Faces	Lumens (per head)	Lumens (per fixture)	Housing Material	Housing Color	Letter Color	Remote Capacity	Self Diagnostic
ECOMBO34	Universal Single/ Double Face	42 lm	84 lm	Thermoplastic	White	Red	No	No
ECOMBO34-G	Universal Single/ Double Face	42 lm	84 lm	Thermoplastic	White	Green	No	No
ECOMBO34-GH	Universal Single/ Double Face	110 lm	220 lm	Thermoplastic	White	Green	No	No
ECOMBO34-GR	Universal Single/ Double Face	42 lm	84 lm	Thermoplastic	White	Green	Yes	No
ECOMBO34-H	Universal Single/ Double Face	110 lm	220 lm	Thermoplastic	White	Red	No	No
ECOMBO34-R	Universal Single/ Double Face	42 lm	84 lm	Thermoplastic	White	Red	Yes	No
ECOMBO34-RG	Universal Single/ Double Face	42 lm	84 lm	Thermoplastic	White	Red/Green	No	No
ECOMBO34-RGH	Universal Single/ Double Face	110 lm	220 lm	Thermoplastic	White	Red/Green	No	No
ECOMBO34-RGR	COMBO34-RGR Universal Single/ Double Face		84 lm	Thermoplastic	White	Red/Green	Yes	No

# ECOMBO34 Exit Sign



2

#### **TECHNICAL SPECIFICATIONS**

#### **CONSTRUCTION**

**Product Type** 

Exit Combo

Shape

Rectangle

**Housing Material** 

Thermoplastic

**Panel Material** 

Thermoplastic

**Panel Color** 

White

**Letter Color** 

Red, green, red/green

**Housing Color** 

White

**Number of Faces** 

Universal single/double face

**Arrow Direction** 

Field-installable chevrons included

**Arrow Material** 

Plastic

Sign Format

Stencil

**Remote Capacity** 

Yes\*

No. of Heads

2 Lamp Heads

**Head Shape** 

Round

**Remote Heads Replaceable** 

Yes\*

#### **ELECTRICAL**

Input Voltage

120-277V

**Operating Frequency** 

60Hz

**Operating Temperature** 

32°F to 104°F (0°C to 40°C)

**Emergency Illumination** 

90 minutes\*

**Battery Backup** 

Yes\*

**Battery Type** 

Nickel Cadmium\*

**Battery Voltage** 

3.6V\*

Recharge Time Required

24 hours\*

**Storage Temperatue** 

68°F to 86°F (20°C to 30°C)\*

Storage Shelf Life

3 years before the initial charge. 5 years after initial charge. \*

**Self Diagnostics** 

No

#### **INSTALLATION**

**Mounting Method** 

Back/Top

**Mounting Type** 

Wall/Ceiling Mount

**Cold Weather Rated** 

No

#### **COMPLIANCE**

Listings

UL924 Listed

**Environment** 

Suitable for use in dry and damp environments.

California Title 20 Compliant

Can be used to conform with the requirements of California Title 20.

California Title 24 JA8 Compliant

Nο

California Energy Commission (CEC) Status

Lawful for Sales in California

FCC

Complies with Part 15 of the FCC Rules.

#### **OTHER**

#### Warranty

The RAB 5-year, limited warranty covers light output, driver perfomance, paint finish and labor.

RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Battery is prorated.

Note


All values are typical (tolerance +/- 10%)


\*Select models



# **DIMENSIONS**

ECOMBO34 Weight: 1.46 lbs





# **ACCESSORIES (SOLD SEPARATELY)**







Catalog Number	UPC	Description			
EREMOTE-1	192552021869	Single remote head			
EREMOTEOUT-1	192552033336	Single remote head, outdoor			
EREMOTE-RTS	192552021944	Emergency remote test button switch			

Single Remote Head

Single Remote Head Outdoor

Emergency Remote Test Switch

# **ORDERING INFO**

Catalog Number	Certification Model Number	UPC	Case Pack
ECOMBO34-R	CEU3RWRC-V2	192552019873	6
ECOMBO34-H	CEU3RW-HL	192552019880	6
ECOMBO34	CEU3RW-V2	192552019897	6
ECOMBO34-GR	CEU3GWRC-V2	192552021593	6
ECOMBO34-GH	CEU3GW-HL	192552021609	6
ECOMBO34-G	CEU3GW-V2	192552021616	6
ECOMBO34-RGR	CEU3RGWRC	192552027069	6
ECOMBO34-RGH	CEU3RGW-HL	192552027076	6
ECOMBO34-RG	CEU3RGW	192552027083	6

# **ORDERING MATRIX**

Family	Family Face		Heads		Exit Sign Letter Color		High Lumen		Remote Capacity	
ECOMBO34	-									
	Blank	Universal Faces	Blank	2 Heads	Blank	Red	Blank	No	Blank	No
					G	Green	Н	High Lumen	R	Remote Capacity
					RG	Red/Green Selectable				