

EXIT34 Exit Sign



EXIT34



EXIT34 Black

PROJECT: _____

DATE: _____

TYPE: _____

PREPARED BY: _____



- ### KEY FEATURES
- Universal or Double-face panel with red or green letters
 - Durable thermoplastic design
 - Options with 90-minutes of emergency illumination
 - Mounting options for wall/ceiling surface mount
 - Select models compliant with California Title 20

Ultra-economy Exit Sign



*Select models

PERFORMANCE

Catalog Number	# of Faces	Housing Color	Panel Color	Letter Color	Arrow Direction	Battery Backup	Mounting	Remote Capacity	Self Diagnostic	IP Rating
EXIT34	Universal Single/Double Face	White	White	Red	No Arrow	None	Wall/Ceiling Mount	No	No	Indoor
EXIT34-G/E	Universal Single/Double Face	White	White	Green	No Arrow	None	Wall/Ceiling Mount	No	No	Indoor
EXIT34-G	Universal Single/Double Face	White	White	Green	No Arrow	90 minutes	Wall/Ceiling Mount	No	No	Indoor
EXIT34-RG	Universal Single/Double Face	White	White	Red/Green, Interchangeable	No Arrow	None	Wall/Ceiling Mount	No	No	Indoor
EXIT34-RG/E	Universal Single/Double Face	White	White	Red/Green, Interchangeable	No Arrow	90 minutes	Wall/Ceiling Mount	No	No	Indoor
EXIT34-RG/E-B	Universal Single/Double Face	Black	Black	Red/Green, Interchangeable	No Arrow	90 minutes	Wall/ Ceiling Mount	Yes	No	Indoor

TECHNICAL SPECIFICATIONS

CONSTRUCTION

Product Type Exit sign	Housing Color White, black*
Shape Rectangle	Number of Faces Universal single/double face
Housing Material Thermoplastic	Arrow Direction No arrows
Panel Material Thermoplastic	Sign Format Stencil
Panel Color White, black*	Remote Capacity No
Letter Color Red, green, red/green	Number of Heads None

ELECTRICAL

Input Voltage 120-277V
Operating Frequency 60Hz
Operating Temperature 32°F to 122°F (0°C to 50°C)
Emergency Illumination 90 minutes*
Battery Backup Yes*
Battery Type Nickel Cadmium*

*Select models

TECHNICAL SPECIFICATIONS (CONT.)

ELECTRICAL

Battery Voltage

1.2V*

Recharge Time Required

24 hours*

Storage Temperature

68°F to 86°F (20°C to 30°C)*

Storage Shelf Life

3 years before the initial charge. 5 years after initial charge. *

Self Diagnostics

No

INSTALLATION

Mounting Method

Back/top/end

Mounting Type

Wall/ceiling mount

Cold Weather Rated

No

COMPLIANCE

Listings

UL924 Listed, NFPA 101 (*current Life Safety Code*), NEC and OSHA illumination standards

Environment

Suitable for indoor use in dry and damp environments.

IP Rating

Indoor

T20 Compliant

Can be used to conform with the requirements of California Title 20.

California Title 24 JA8 Compliant

No

California Energy Commission (CEC) Status

Lawful for Sales in California

FCC

Complies with Part 15 of the FCC Rules.

OTHER

Warranty

"The RAB 5-year, limited warranty covers light output, driver performance, paint finish and labor.

RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Battery is prorated.

Note

All values are typical (tolerance +/- 10%)

ACCESSORIES

Emergency Remote Test Switch





Catalog Number	UPC	Description
EREMOTE-RTS	192552021944	Emergency remote test button switch

DIMENSIONS



EXIT34

Weight: 1.69 lbs



EXIT34 Black

Weight: 1.69 lbs



EXIT34 Exit Sign



ORDERING INFO

Catalog Number	Certification Model Number	UPC	Case Pack
EXIT34	EZRXTU2RW-V2	192552019804	6
EXIT34-G/E	EZRXTU2GWEM-V2	192552019811	6
EXIT34-G	EZRXTU2GW-V2	192552019828	6
EXIT34-RG	EZRXTU2RGW	192552026888	6
EXIT34-RG/E	EZRXTU2RGWEM	192552026895	6
EXIT34-RG/E-B	EZRXTU2RBEM-V2	192552036504	6

ORDERING MATRIX

Family	Face	Exit Sign Letter Color	Battery Backup	Housing
EXIT34	<input type="checkbox"/> - Blank Universal	<input type="checkbox"/> Blank G Red RG Green Red/Green Interchangeable	<input type="checkbox"/> Blank No /E Battery Backup	<input type="checkbox"/> - Blank White B Black