

Reflectors, Static CCT



BR40

BR30

65-85W Equivalent, 120V



80 & 90 CRI*



15,000 HOURS



DAMP RATED



120V



DIMMABLE



ENCLOSED FIGURE

*Select Models

PROJECT:

DATE:

TYPE:

PREPARED BY:



KEY FEATURES

- Energy-efficient replacement for incandescent and halogen reflector lamps
- Construction from durable plastic which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Frosted lens delivers smooth, diffuse light
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

PERFORMANCE

Catalog Number	Shape	Wattage Equivalency	Input Wattage	Lumens	Efficacy	Color Temp	CRI
BR40-11-827-DIM	BR40	85W Halogen	13W	1,100 lm	85 lm/W	2700K	>80
BR40-11-830-DIM						3000K	
BR30-10-927-DIM	BR30	65W Halogen	9.5W	800 lm	84 lm/W	2700K	>90
BR30-10-930-DIM						3000K	
BR30-10-940-DIM						4000K	
BR30-10-950-DIM						5000K	

TECHNICAL SPECIFICATIONS

CONSTRUCTION

Product Type

Reflector, 80 CRI Dimmable

Shape

BR30, BR40

Endcap Material

Nickel-plated aluminum

Enclosure Material

Polycarbonate

Finish

White

Base Type

E26 Edison

LED CHARACTERISTICS

Beam Angle

120°

Color Temperature

2700/3000/4000*/5000K*

Color Accuracy (CRI)

BR30: 90CRI; BR40: 80CRI

R9 Value

High color performance with R9 greater than 0

Color Consistency

<7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

* Not available for BR40

ELECTRICAL

Dimmable

TRIAC/ELV dimming systems. See Dimmer List

Input Voltage

120V

Operating Temperature

-4°F to 104°F (-20°C to 40°C)

THD

<75%

Power Factor

0.9

Flicker

≤30%

COMPLIANCE

ETL Listed

This product has been tested by Intertek and found in compliance with accepted national standards.

Environment

Suitable for use indoors in dry and damp environments.

Fixture Rating

Suitable for use in enclosed fixtures

Energy Star Approved

No

DLC Listed

No

California Title 20 Compliant*

Can be used to conform with the requirements of California Title 20.

California Title 24 JA8 Compliant*

Can be used to conform with the requirements of California Title 24 Part 6

California Energy Commission (CEC)

Lawful for Sales in California

IESNA LM-79 & LM80 Testing

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS

Mercury and UV free. RoHS-compliant components.

FCC

Complies with Part 15 of the FCC Rules

*Select models

OTHER


Warranty

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

DIMENSIONS


BR40

Weight: 0.31 lbs.



BR30

Weight: 0.31 lbs.



ORDERING INFO

Catalog Number	Model Number	UPC	Case Pack
BR40-11-827-DIM	P30009(BR40-11-827-DIM)	19813835662	6
BR40-11-830-DIM	P30010(BR40-11-830-DIM)	192552052665	6
BR30-10-927-DIM	P30005(BR30-10-927-DIM)	19813750071	6
BR30-10-930-DIM	P30006(BR30-10-930-DIM)	19813750088	6
BR30-10-940-DIM	P30007(BR30-10-940-DIM)	19813750095	6
BR30-10-950-DIM	P30008(BR30-10-950-DIM)	19813835655	6

ORDERING MATRIX

Family	Wattage	Base Type	CRI/Color Temp	Voltage/Dimming
BR30	10			DIM
10	10W	Blank E26 Edison	927 930 940 950	DIM 120V; TRIAC/ELV 90 CRI, 2700K 90 CRI, 3000K 90 CRI, 4000K 90 CRI, 5000K

Family	Wattage	Base Type	CRI/Color Temp	Voltage/Dimming
BR40	11			DIM
11	11W	Blank E26 Edison	827 830	DIM 120V; TRIAC/ELV 80 CRI, 2700K 80 CRI, 3000K

Dimmer Compatibility List

BR30 & B40		Dimmer compatibility								
Brand	Dimmer Cat NR	1 Lamp	2 Lamp	3 Lamp	4 Lamp	5 Lamp	6 Lamp	Max Watt	Min Watt	Dimming Level <10%
LUTRON	MAELV-600	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
LUTRON	CTCL-153P	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
LUTRON	DVCL-153P	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
LUTRON	TGCL-153P	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
LEVITON	6672	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
LEGRAND	IPL06	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓
RAB	XDIM	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓