


SLIM Amber Wall Pack



PROJECT:

DATE:

TYPE:

PREPARED BY:

Amber wall pack with field-adjustable wattages



0-10V



EASY INSTALL



IP RATING



100,000
HRS



WET
RATED



POWER
ADJUSTABLE

PERFORMANCE

SLIM	AMBER		
Wattage	26W	18W	12W
Input Watts	29.2W	21.5W	14.3W
Lumens	1,190	1,144	922
Efficacy	40.8	53.2	64.5
Voltage Ratings	120-277V		

KEY FEATURES

- Field-adjustable wattages:
26/18/12W
- Wildlife friendly **amber** Light, wavelength 585 - 595 nm
- Integrated **on/off** photocell
- 0-10V** dimming
- UL rated for **wet** location
- IP65** rated
- 10-year**, no-compromise warranty



TECHNICAL SPECIFICATIONS

COMPLIANCE

UL Listed

This product is UL listed for wet locations

ADA Compliant

Meets ADA Requirements for wall-mounted luminaires.

DarkSky Certified

All SLIM amber models are certified by DarkSky as a Sea Turtle Sensitive Luminaire which must include shielding and color spectra tuned to protect specific species habitats.

LED CHARACTERISTICS

LEDs

Long-life, high-efficacy, surface-mount LEDs

FIELD ADJUSTABLE

Adjustable Wattage: 26/18/12W - Factory default 26W

Color Temperature: Amber

TECHNICAL SPECIFICATIONS

CONSTRUCTION

IP Rating

Ingress protection rating of IP65 for dust and water

Cold Weather Starting

Minimum starting temperature is -40°C (-40°F)

Maximum Ambient Temperature

Suitable for use in up to 40°C (40°F)

Housing

Bronze and White: Aluminum

Brass: Brass

Mounting

Heavy-duty mounting bracket with spring-hinged housing and "kick stand" allow for easy installations. Conduit entries on back and both sides.

Lens

Acrylonitrile styrene acrylate (ASA) /Acrylonitrile butadiene styrene (ABS)

Photocell

Integrated photocell included with on/off switch

Reflector Material

Mirror finish on polycarbonate

Green Technology

Mercury and UV free. RoHS-compliant components.

Finish

Bronze & White: Formulated for high durability and long-lasting color

Brass: Brushed and electroplated finish that will naturally patina over time

ELECTRICAL

Drivers:

Constant Current, Class 2, 120-277V, 50/60 Hz

26W: 120V: 0.26A, 208V: 0.13A, 240V: 0.12A, 277V: 0.11A

18W: 120V: 0.20A, 208V: 0.10A, 240V: 0.09A, 277V: 0.08A

12W: 120V: 0.13A, 208V: 0.07A, 240V: 0.06A, 277V: 0.06A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

26W: 2.8% at 120V, 4.9% at 277V

18W: 3.8% at 120V, 5.6% at 277V

12W: 4.0% at 120V, 9.5% at 277V

Power factor:

26W: 99.8% at 120V, 96.6% at 277V

18W: 99.6% at 120V, 94.3% at 277V

12W: 99.2% at 120V, 88.8% at 277V

Surge Protection

4kV

Note

All values are typical (tolerance +/- 10%)

OTHER

Warranty

The RAB 10-year, no-compromise warranty covers light output, color stability, driver performance, paint finish and labor. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Lifespan


100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

DIMENSIONS

SLIM

Weight: (White and Bronze) 2.9 lbs

Weight: (Brass) 5.7 lbs



SLIM Amber Wall Pack



ORDERING MATRIX

FAMILY	WATTAGE	WAVELENGTH	FINISH	DRIVER
SLIM	<div>BLANK26/18/12W</div>	<div>YA Amber</div>	<div>BLANK W BR Bronze White Solid Brass</div>	<div>BLANK120-277V, 0-10V Dimming</div>