

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 1 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

LUMINAIRE: CAST FINNED METAL HOUSING, 6 CHIP ON BOARD LIGHT EMITTING DIODES, MOLDED PLASTIC REFLECTOR WITH SPECULAR FINISH, CLEAR GLASS LENS IN CAST BRONZE PAINTED METAL FRAME.

LAMPS: SIX WHITE MULTI-CHIP LIGHT EMITTING DIODES (LEDs), 2 LEDs TILTED 63-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 75-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 67-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 68-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 58-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 40-DEGREES FROM STRAIGHT AHEAD.


ABSOLUTE: NOTE: THIS REPORT WAS PRORATED FROM RAB04286 WHICH WAS ALED2T150Y. ACTUAL PERFORMANCE MAY VARY.

WATT: TOTAL INPUT WATTS = 52.1 W AT 277.0 VAC.

LED DRIVER: LED DRIVER: RD-052-A1400-R

PROCEDURE: TEST PROCEDURE: IESNA LM-79-08

NOTE: LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE



Checked X.CAO

Approved D.WANG-MUNSON

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 2 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)


ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION
Values based on 25-foot mounting height

IES Classification: Medium, Type II

Cutoff Classification (deprecated): Semicutoff

--- 1/2 Maximum Candela trace

× Maximum Candela point



REPORT NUMBER: PRORATED FROM RAB04286


PAGE: 3 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA



REPORT NUMBER: PRORATED FROM RAB04286


PAGE: 4 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY. THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 5 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

BUG Rating			B1 U0 G2		
Zonal Summary			Zone Ratings		
			B	U	G
Forward					
FL	(0° – 30°)	5673			
FM	(30° – 60°)	637.9			
FH	(60° – 80°)	2782.5			
FVH	(80° – 90°)	2214.0			G2
		38.6			G1
Backward					
BL	(0° – 30°)	1331			
BM	(30° – 60°)	372.5	B1		
BH	(60° – 80°)	634.2	B1		
BVH	(80° – 90°)	318.1	B1		G1
		6.1			G0
Upward					
UL	(90° – 100°)	0			
UH	(100° – 180°)	0.0		U0	
		0.0		U0	
Trapped Light					
Total Flux					
		0			
		7004			
		100.0			

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 6 OF 10


ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

Zonal Lumen Summary

(Linear scale)



REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 7 OF 10


ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)


Backlight Rating Details

(Logarithmic scale)




Uplight Rating Details

(Logarithmic scale)



Glare Rating Details

(Logarithmic scale)



REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 8 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

CANDELA TABULATION											
	STREET SIDE			LATERAL ANGLE							
	0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0	80.0	85.0
180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
87.5	0.	0.	1.	2.	4.	4.	5.	12.	8.	7.	5.
85.0	1.	1.	3.	3.	5.	10.	35.	21.	24.	26.	24.
V 82.5	4.	3.	5.	8.	34.	78.	154.	191.	221.	198.	129.
E 80.0	8.	7.	29.	74.	127.	246.	547.	726.	899.	759.	460.
R 77.5	15.	16.	96.	175.	321.	642.	1207.	1978.	2412.	2297.	1511.
T 75.0	26.	49.	187.	356.	654.	1087.	1812.	3092.	4667.	4533.	3384.
I 72.5	64.	119.	319.	589.	982.	1604.	2513.	3481.	5898.	6229.	5153.
C 70.0<<	150.	212.	460.	830.	1347.	2152.	3107.	3939.	6011.	6443.	5921.
A 67.5	289.	306.	638.	1101.	1748.	2675.	3379.	4426.	5034.	5584.	5334.
L 65.0	453.	447.	857.	1405.	2160.	3035.	3647.	4633.	4666.	4441.	4336.
62.5	603.	626.	1081.	1712.	2432.	3183.	3745.	4633.	4274.	3964.	3588.
A 60.0	739.	811.	1275.	1886.	2590.	3251.	3865.	4465.	4134.	3829.	3401.
N 57.5	856.	966.	1375.	2012.	2604.	3215.	3926.	4119.	3973.	3831.	3273.
G 55.0	1009.	1089.	1445.	2018.	2612.	3255.	3872.	3931.	3754.	3520.	3073.
L 52.5	1163.	1213.	1478.	2096.	2681.	3327.	3695.	3711.	3321.	3032.	2729.
E 50.0	1331.	1347.	1583.	2184.	2783.	3282.	3557.	3420.	2983.	2737.	2397.
47.5	1459.	1491.	1716.	2266.	2787.	3082.	3310.	3112.	2685.	2502.	2290.
45.0	1559.	1602.	1817.	2277.	2703.	2869.	2888.	2831.	2539.	2337.	2213.
42.5	1632.	1680.	1864.	2211.	2496.	2687.	2572.	2541.	2345.	2251.	2163.
40.0	1662.	1694.	1860.	2052.	2330.	2471.	2461.	2348.	2209.	2174.	2083.
37.5	1636.	1648.	1831.	1924.	2129.	2330.	2310.	2263.	2148.	2101.	1994.
35.0	1586.	1583.	1696.	1751.	1968.	2122.	2194.	2231.	2039.	1964.	1879.
32.5	1527.	1531.	1634.	1664.	1804.	1938.	2088.	2133.	1992.	1913.	1849.
30.0	1484.	1508.	1614.	1630.	1752.	1823.	1954.	1959.	1870.	1851.	1805.
25.0	1412.	1430.	1484.	1558.	1545.	1612.	1670.	1674.	1672.	1672.	1622.
20.0	1351.	1352.	1392.	1495.	1510.	1521.	1480.	1507.	1520.	1490.	1461.
15.0	1365.	1356.	1375.	1423.	1473.	1479.	1469.	1473.	1423.	1394.	1371.
10.0	1331.	1331.	1342.	1348.	1381.	1409.	1424.	1421.	1409.	1394.	1384.
5.0	1304.	1306.	1310.	1310.	1314.	1308.	1308.	1306.	1315.	1301.	1292.
0.0	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.
										PLANE OF MAXIMUM CANDELA	
										CONE OF MAXIMUM CANDELA	

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 9 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

CANDELA TABULATION												
	HOUSE	SIDE	LATERAL ANGLE									
			90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0
V E R T I C A L A N G L E	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	4.	4.	4.	3.	3.	3.	3.	2.	1.	1.	1.
	85.0	12.	8.	5.	4.	4.	4.	3.	2.	2.	1.	1.
	82.5	101.	43.	31.	10.	6.	5.	4.	5.	5.	4.	4.
	80.0	400.	216.	98.	36.	15.	5.	5.	6.	6.	5.	4.
	77.5	1175.	570.	95.	31.	14.	5.	5.	6.	6.	5.	5.
	75.0	2449.	955.	116.	47.	14.	9.	5.	6.	5.	5.	5.
	72.5	3716.	1294.	465.	117.	15.	11.	5.	5.	5.	5.	5.
	70.0<<	4351.	1658.	676.	184.	23.	11.	6.	7.	6.	5.	5.
	67.5	4115.	2068.	1040.	239.	31.	12.	7.	7.	7.	5.	5.
	65.0	3489.	2046.	1342.	288.	77.	17.	10.	8.	8.	6.	5.
	62.5	3063.	2063.	1133.	336.	187.	34.	14.	10.	9.	8.	6.
	60.0	2919.	2157.	1066.	427.	316.	49.	19.	18.	19.	11.	7.
	57.5	2744.	2140.	969.	468.	393.	105.	25.	21.	26.	13.	7.
	55.0	2587.	2148.	907.	509.	392.	171.	35.	25.	34.	13.	8.
	52.5	2370.	2115.	1009.	599.	377.	216.	90.	30.	38.	12.	10.
	50.0	2134.	1994.	1070.	715.	404.	224.	143.	63.	27.	15.	12.
	47.5	2089.	1931.	1098.	744.	412.	218.	174.	109.	60.	36.	28.
	45.0	2073.	1878.	1144.	741.	423.	248.	178.	142.	118.	65.	52.
	42.5	2028.	1821.	1215.	756.	439.	282.	172.	147.	130.	85.	69.
	40.0	1956.	1749.	1332.	795.	477.	309.	200.	142.	124.	89.	75.
	37.5	1886.	1712.	1426.	840.	534.	341.	241.	167.	111.	89.	79.
	35.0	1777.	1698.	1430.	903.	576.	394.	271.	212.	134.	104.	94.
	32.5	1757.	1704.	1447.	964.	636.	441.	309.	244.	170.	134.	122.
	30.0	1713.	1665.	1414.	1025.	714.	484.	348.	266.	192.	173.	163.
25.0	1581.	1538.	1347.	1160.	833.	622.	450.	336.	272.	253.	245.	
20.0	1443.	1426.	1290.	1142.	979.	783.	639.	512.	440.	418.	403.	
15.0	1359.	1356.	1287.	1200.	1118.	1024.	899.	774.	713.	707.	686.	
10.0	1367.	1364.	1318.	1267.	1198.	1134.	1067.	1008.	979.	951.	942.	
5.0	1279.	1273.	1258.	1248.	1232.	1204.	1185.	1180.	1164.	1158.	1147.	
0.0	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	1272.	

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 10 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T50 - RWLED2T50 - RWLED2T50SF - WPLED2T50 (TYPE II)

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	30
5- 10	90
10- 15	148
15- 20	195
20- 25	244
25- 30	304
30- 35	371
35- 40	445
40- 45	528
45- 50	617
50- 55	694
55- 60	761
60- 65	792
65- 70	795
70- 75	655
75- 80	290
80- 85	43
85- 90	2
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	120
0- 20	463
0- 30	1010
0- 40	1827
0- 50	2972
0- 60	4427
0- 70	6015
0- 80	6959
0- 90	7004
0-100	7004
0-110	7004
0-120	7004
0-130	7004
0-140	7004
0-150	7004
0-160	7004
0-170	7004
0-180	7004