

REPORT NUMBER: RAB04359

PAGE: 1 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

LUMINAIRE: CAST FINNED METAL HOUSING, 6 CIRCUIT BOARDS EACH WITH 1 LED,
MOLDED PLASTIC REFLECTOR WITH SPECULAR FINISH AND 1 APERTURE PER LED,
CLEAR FLAT GLASS LENS IN CAST BROWN PAINTED METAL LENS FRAME.


LAMPS: SIX WHITE MULTI-CHIP LIGHT EMITTING DIODES (LEDs), 2 LEDs TILTED
63-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 75-DEGREES FROM
STRAIGHT AHEAD, 2 LEDs TILTED 67-DEGREES FROM VERTICAL BASE-UP POSITION
AND CANTED 68-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 58-DEGREES FROM
VERTICAL BASE-UP POSITION AND CANTED 40-DEGREES FROM STRAIGHT AHEAD.

ABSOLUTE: NOTE: THIS REPORT WAS PRORATED FROM RAB04359 WHICH WAS
ALED3T66Y/480. ACTUAL PERFORMANCE MAY VARY.

WATT: TOTAL INPUT WATTS = 67.0 W AT 480.0 VAC.

LED DRIVER: LED DRIVER: RDD-H65-36A-A1400-480

NOTE: LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE



Checked X.CAO

Approved D.WANG-MUNSON

REPORT NUMBER: RAB04359

PAGE: 2 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION


Values based on 25-foot mounting height

IES Classification: Short, Type III

Cutoff Classification (deprecated): Semicutoff

— — — — — 1/2 Maximum Candela trace

× Maximum Candela point



REPORT NUMBER: RAB04359


PAGE: 3 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.


CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA



REPORT NUMBER: RAB04359 **PAGE:** 4 OF 10
ISSUE DATE: 05/09/18
PREPARED FOR: RAB LIGHTING INC.
CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
 WPLED3T66/480 (TYPE III)

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
 THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
 LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: RAB04359

PAGE: 5 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

BUG Rating			B1 U0 G2		
Zonal Summary			Zone Ratings		
			B	U	G
Forward					
FL	(0° – 30°)	7338			
FM	(30° – 60°)	785.2			
FH	(60° – 80°)	3469.3			
FVH	(80° – 90°)	2973.0			G2
		111.0			G2
Backward					
BL	(0° – 30°)	793			
BM	(30° – 60°)	185.3	B1		
BH	(60° – 80°)	408.8	B1		
BVH	(80° – 90°)	195.0	B1		G1
		4.3			G0
Upward					
UL	(90° – 100°)	0			
UH	(100° – 180°)	0.0		U0	
		0.0		U0	
Trapped Light					
Total Flux					
		0			
		8132			
		100.0			

REPORT NUMBER: RAB04359

PAGE: 6 OF 10


ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

Zonal Lumen Summary

(Linear scale)




PAGE: 7 OF 10




PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

(Logarithmic scale)



(Logarithmic scale)



REPORT NUMBER: RAB04359

PAGE: 8 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

CANDELA TABULATION

	STREET SIDE										
	0.0	5.0	15.0	25.0	35.0	45.0	52.5	55.0	65.0	75.0	85.0
180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
87.5	1.	2.	2.	3.	6.	8.	9.	9.	11.	8.	7.
85.0	10.	10.	24.	46.	57.	97.	84.	79.	125.	94.	16.
V 82.5	34.	63.	153.	205.	278.	370.	519.	561.	799.	557.	117.
E 80.0	110.	171.	307.	497.	655.	1062.	1353.	1450.	1598.	1159.	524.
R 77.5	413.	484.	650.	1060.	1275.	1663.	2100.	2215.	2663.	2041.	1290.
T 75.0	884.	917.	1114.	1551.	1859.	2310.	2701.	2787.	3465.	2796.	1697.
I 72.5	1274.	1265.	1462.	1954.	2340.	3058.	3640.	3720.	4427.	3662.	2217.
C 70.0	1509.	1504.	1753.	2334.	2776.	3930.	4698.	4881.	4819.	4533.	3120.
A 67.5<<	1818.	1785.	2090.	2725.	3385.	4652.	5144.	5078.	4844.	4766.	3783.
L 65.0	2096.	2045.	2416.	3144.	4033.	5074.	4810.	4716.	4686.	4883.	4106.
62.5	2537.	2530.	2962.	3766.	4652.	4773.	4703.	4610.	4388.	4951.	4067.
A 60.0	3328.	3333.	3717.	4468.	4708.	4510.	4310.	4248.	4416.	4839.	3910.
N 57.5	3996.	4031.	4239.	4446.	4233.	4001.	3898.	3965.	4627.	4495.	3644.
G 55.0	4056.	4044.	4015.	3797.	3719.	3559.	3700.	3671.	4429.	4010.	3330.
L 52.5	3450.	3444.	3471.	3341.	3266.	3328.	3473.	3672.	3857.	3604.	2864.
E 50.0	3046.	3056.	3095.	2986.	2907.	3355.	3441.	3526.	3535.	3277.	2402.
47.5	2823.	2823.	2786.	2720.	2813.	3062.	3283.	3269.	3171.	3008.	2254.
45.0	2634.	2637.	2558.	2577.	2849.	2945.	2954.	2895.	2888.	2813.	2042.
42.5	2451.	2458.	2468.	2716.	2728.	2824.	2770.	2757.	2671.	2643.	1843.
40.0	2440.	2451.	2507.	2582.	2681.	2634.	2635.	2598.	2503.	2502.	1702.
37.5	2310.	2290.	2370.	2632.	2505.	2565.	2464.	2411.	2345.	2273.	1622.
35.0	2321.	2332.	2455.	2517.	2530.	2499.	2403.	2351.	2330.	2135.	1539.
32.5	2471.	2444.	2377.	2405.	2508.	2421.	2316.	2289.	2302.	2145.	1506.
30.0	2445.	2420.	2350.	2383.	2390.	2267.	2207.	2207.	2253.	2103.	1484.
25.0	2531.	2509.	2326.	2237.	2147.	2095.	2065.	2072.	2043.	1748.	1287.
20.0	2365.	2362.	2232.	2099.	2024.	1994.	1973.	1951.	1800.	1497.	1129.
15.0	2112.	2112.	2073.	1993.	1930.	1867.	1797.	1772.	1565.	1272.	1005.
10.0	1929.	1925.	1927.	1837.	1743.	1582.	1466.	1438.	1268.	1082.	910.
5.0	1417.	1404.	1403.	1359.	1309.	1226.	1163.	1149.	1050.	970.	899.
0.0	892.	892.	892.	892.	892.	892.	892.	892.	892.	892.	892.

PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA

REPORT NUMBER: RAB04359

PAGE: 9 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

CANDELA TABULATION

HOUSE SIDE		LATERAL ANGLE									
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0 180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	6.	6.	6.	6.	6.	5.	4.	3.	3.	3.
	85.0	9.	8.	7.	7.	5.	5.	4.	3.	2.	2.
V	82.5	47.	28.	13.	9.	6.	4.	4.	3.	3.	3.
E	80.0	269.	135.	32.	19.	7.	4.	3.	3.	3.	3.
R	77.5	667.	342.	74.	30.	10.	4.	3.	3.	4.	4.
T	75.0	954.	480.	141.	38.	21.	8.	4.	3.	4.	3.
I	72.5	1332.	671.	198.	94.	52.	12.	8.	4.	5.	5.
C	70.0	1930.	965.	465.	161.	57.	14.	14.	5.	6.	6.
A	67.5<<	2394.	1133.	629.	219.	64.	24.	10.	6.	6.	6.
L	65.0	2564.	1194.	625.	275.	75.	45.	22.	7.	5.	6.
	62.5	2676.	1230.	660.	336.	97.	64.	43.	13.	7.	5.
A	60.0	2433.	1236.	731.	389.	125.	91.	52.	20.	8.	5.
N	57.5	2323.	1231.	715.	379.	157.	113.	60.	25.	11.	5.
G	55.0	2158.	1266.	668.	393.	190.	123.	69.	33.	14.	6.
L	52.5	1946.	1248.	591.	407.	252.	130.	77.	39.	18.	7.
E	50.0	1757.	1238.	582.	467.	323.	158.	83.	44.	23.	30.
	47.5	1658.	1157.	622.	419.	311.	172.	100.	50.	30.	38.
	45.0	1567.	1119.	620.	424.	296.	183.	112.	62.	44.	36.
	42.5	1501.	1135.	647.	421.	318.	198.	121.	100.	60.	36.
	40.0	1406.	1186.	706.	426.	339.	208.	131.	88.	74.	49.
	37.5	1340.	1169.	941.	480.	337.	220.	147.	95.	82.	62.
	35.0	1288.	1130.	947.	631.	385.	276.	164.	109.	83.	66.
	32.5	1263.	1099.	844.	618.	465.	319.	189.	115.	85.	68.
	30.0	1199.	1046.	784.	548.	384.	300.	250.	125.	87.	69.
	25.0	1068.	938.	707.	552.	367.	270.	201.	152.	111.	95.
	20.0	964.	861.	688.	578.	436.	298.	216.	171.	161.	154.
	15.0	881.	799.	691.	583.	511.	449.	365.	289.	253.	216.
	10.0	833.	771.	677.	614.	555.	517.	488.	453.	416.	387.
	5.0	860.	832.	767.	717.	674.	636.	618.	593.	581.	571.
	0.0	892.	892.	892.	892.	892.	892.	892.	892.	892.	892.

CONE OF MAXIMUM CANDELA

REPORT NUMBER: RAB04359

PAGE: 10 OF 10

ISSUE DATE: 05/09/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T66/480 - RWLED3T66/480 - RWLED3T66SF/480 -
WPLED3T66/480 (TYPE III)

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	22
5- 10	70
10- 15	127
15- 20	185
20- 25	248
25- 30	318
30- 35	394
35- 40	458
40- 45	539
45- 50	650
50- 55	818
55- 60	1019
60- 65	1056
65- 70	979
70- 75	731
75- 80	402
80- 85	109
85- 90	6
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	92
0- 20	404
0- 30	971
0- 40	1823
0- 50	3012
0- 60	4849
0- 70	6883
0- 80	8017
0- 90	8132
0-100	8132
0-110	8132
0-120	8132
0-130	8132
0-140	8132
0-150	8132
0-160	8132
0-170	8132
0-180	8132