


ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION

Values based on 3.5 foot mounting height.



REPORT NUMBER: PRORATED FROM RAB03691
ISSUE DATE: 08/30/17 PAGE: 1 OF 9
PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

CATALOG NUMBER: BLEDR18, BLEDR18/D10, BDLEDR18, BDLEDR18/D10 (42" ROUND BOLLARD), WBLEDR18/D10

LUMINAIRE: EXTRUDED BROWN PAINTED CYLINDRICAL METAL LOWER HOUSING, CAST METAL TOP, CAST FINNED METAL HEAT SINK WITH WHITE PAINTED INTERIOR, MOLDED SPECULAR FINISHED PLASTIC REFLECTOR, 3 WHITE CIRCUIT BOARDS EACH WITH 3 LEDS, 3 WHITE CIRCUIT BOARDS EACH WITH 2 LEDS, FROSTED PLASTIC LENS, CAST BROWN PAINTED METAL BOTTOM.


LAMP: FIFTEEN LIGHT EMITTING DIODES (LEDS).

(SEE PAGE 2 FOR MORE INFORMATION)

IES Cutoff Classification: Noncutoff

--- 1/2 Maximum Candela trace

X Maximum Candela point



REPORT NUMBER: PRORATED FROM RAB03691
ISSUE DATE: 08/30/17
PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 2 OF 9

ADDITIONAL INFORMATION

NOTE: THIS REPORT WAS PRORATED FROM RAB03691 WHICH WAS BLEDR18Y,
BLEDR18Y/D10, BDLEDR18Y, BDLEDR18Y/D10. ACTUAL PERFORMANCE MAY
VARY.

TOTAL INPUT WATTS = 17.3 W AT 277.0 VAC.


LED DRIVER: RD-LU018-A035C0SP

TEST PROCEDURE: IESNA LM-79-08

LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA


REPORT NUMBER: PRORATED FROM RAB03691
 ISSUE DATE: 08/30/17 PAGE: 3 OF 9
 PREPARED FOR: RAB LIGHTING INC. RC
 LIGHTING
 CATALOG NUMBER: BLEDR18, BLEDR18/D10,
 BDLEDR18, BDLEDR18/D10 (42" ROUND
 BOLLARD), WBLEDR18/D10
 LUMINAIRE: EXTRUDED BROWN PAINTED
 CYLINDRICAL METAL LOWER HOUSING, CAST
 METAL TOP, CAST FINNED METAL HEAT
 SINK WITH WHITE PAINTED INTERIOR,
 MOLDED SPECULAR FINISHED PLASTIC
 REFLECTOR, 3 WHITE CIRCUIT BOARDS
 EACH WITH 3 LEDS, 3 WHITE CIRCUIT
 BOARDS EACH WITH 2 LEDS, FROSTED
 PLASTIC LENS, CAST BROWN PAINTED
 METAL BOTTOM.
 LAMP: FIFTEEN LIGHT EMITTING DIODES
 (LEDS).
 (SEE PAGE 2 FOR MORE INFORMATION)



REPORT NUMBER: PRORATED FROM RAB03691
 ISSUE DATE: 08/30/17
 PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 4 OF 9

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



	LUMENS	PERCENT OF FIXTURE
DOWNWARD STREET SIDE	1024.	54.9
DOWNWARD HOUSE SIDE	639.	34.3
DOWNWARD TOTAL	1663.	89.2
UPWARD STREET SIDE	118.	6.3
UPWARD HOUSE SIDE	84.	4.5
UPWARD TOTAL	202.	10.8
TOTAL FLUX	1865.	100.0
TOTAL INPUT WATTS = 17.3		
EFFICACY = 107.8 Lm/W		

ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
 THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
 LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: PRORATED FROM RAB03691

ISSUE DATE: 08/30/17

PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 5 OF 9

BUG Rating:

Zonal Summary

Lumens

% of Fixture

B1 U3 G2

Zone Ratings


B U G

Forward		1024	54.9			
FL	(0° - 30°)	41.4	2.2			
FM	(30° - 60°)	290.2	15.6			
FH	(60° - 80°)	555.1	29.8			G0
FVH	(80° - 90°)	137.7	7.4			G2
Backward		639	34.3			
BL	(0° - 30°)	25.9	1.4	B0		
BM	(30° - 60°)	181.4	9.7	B0		
BH	(60° - 80°)	338.3	18.1	B1		G1
BVH	(80° - 90°)	93.2	5.0			G1
Upward		202	10.8			
UL	(90° - 100°)	94.1	5.0		U3	
UH	(100° - 180°)	107.7	5.8		U3	
Trapped Light		0	0.0			
Total Flux		1865	100.0			

Zonal Lumen Summary

(Linear scale)

UH
107.7 Lm
5.8%




REPORT NUMBER: PRORATED FROM RAB03691
 ISSUE DATE: 08/30/17
 PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 6 OF 9


Backlight Rating Details

(Logarithmic scale)




Glare Rating Details

(Logarithmic scale)



Uplight Rating Details

(Logarithmic scale)



REPORT NUMBER: PRORATED FROM RAB03691
 ISSUE DATE: 08/30/17
 PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 7 OF 9

CANDELA TABULATION

	STREET SIDE	LATERAL ANGLE								
		0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0 85.0
	180.0	1.	1.	1.	1.	1.	1.	1.	1.	1.
	175.0	1.	1.	1.	1.	1.	1.	1.	1.	1.
	165.0	1.	1.	1.	1.	1.	1.	1.	1.	1.
	155.0	1.	1.	1.	1.	1.	1.	1.	1.	1.
	145.0	5.	5.	5.	5.	5.	5.	5.	5.	5.
	135.0	11.	12.	11.	12.	12.	12.	11.	11.	11.
	125.0	21.	21.	21.	21.	21.	21.	20.	20.	19.
	115.0	36.	36.	36.	36.	35.	35.	34.	33.	32.
	105.0	59.	57.	57.	57.	56.	55.	54.	53.	49.
	95.0	103.	102.	101.	101.	100.	98.	96.	94.	88.
	90.0	151.	153.	150.	152.	149.	148.	143.	139.	130.
	87.5	193.	196.	192.	194.	190.	190.	181.	178.	164.
	85.0	252.	256.	252.	255.	249.	248.	236.	232.	221.
V	82.5	329.	334.	330.	334.	327.	325.	310.	302.	288.
E	80.0	423.	427.	424.	428.	423.	420.	399.	388.	368.
R	77.5	527.	533.	529.	534.	527.	522.	501.	482.	457.
T	75.0	640.	645.	642.	642.	632.	623.	595.	572.	541.
I	72.5	722.	724.	719.	712.	699.	685.	657.	628.	592.
C	70.0<<	729.	726.	724.	709.	699.	678.	653.	620.	587.
A	67.5	661.	654.	657.	639.	632.	611.	589.	557.	530.
L	65.0	556.	548.	551.	536.	534.	513.	499.	471.	447.
	62.5	462.	458.	459.	448.	445.	426.	413.	393.	373.
A	60.0	392.	389.	389.	384.	378.	363.	352.	337.	321.
N	57.5	348.	345.	345.	342.	336.	322.	313.	301.	288.
G	55.0	318.	317.	317.	315.	308.	296.	288.	277.	267.
L	52.5	300.	300.	300.	295.	289.	280.	272.	262.	252.
E	50.0	287.	286.	286.	281.	275.	267.	260.	251.	241.
	47.5	275.	274.	273.	268.	262.	256.	249.	240.	232.
	45.0	265.	265.	261.	256.	252.	246.	240.	231.	222.
	42.5	253.	252.	249.	245.	240.	235.	229.	221.	213.
	40.0	241.	241.	238.	233.	228.	224.	219.	211.	203.
	37.5	228.	228.	225.	221.	215.	212.	207.	200.	192.
	35.0	213.	213.	211.	207.	203.	199.	193.	187.	180.
	30.0	177.	178.	177.	173.	171.	167.	162.	156.	149.
	25.0	135.	135.	135.	133.	131.	129.	124.	119.	114.
	20.0	100.	100.	98.	98.	97.	95.	92.	89.	84.
	15.0	78.	78.	78.	77.	76.	75.	73.	70.	67.
	10.0	52.	53.	52.	52.	52.	50.	49.	48.	47.
	5.0	4.	4.	5.	5.	5.	5.	6.	6.	6.
	0.0	0.	0.	0.	0.	0.	0.	0.	0.	0.

||
 PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB03691
 ISSUE DATE: 08/30/17
 PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 8 OF 9

CANDELA TABULATION

HOUSE SIDE		LATERAL ANGLE										
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
V E R T I C A L A N G L E	180.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	175.0	1.	1.	1.	1.	1.	1.	1.	2.	2.	1.	1.
	165.0	1.	1.	1.	1.	1.	1.	1.	2.	2.	2.	1.
	155.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	145.0	5.	4.	4.	4.	4.	4.	4.	2.	2.	2.	2.
	135.0	11.	11.	9.	8.	8.	7.	7.	7.	6.	6.	6.
	125.0	19.	19.	18.	16.	15.	14.	13.	13.	12.	12.	12.
	115.0	32.	30.	29.	27.	26.	25.	22.	21.	21.	20.	21.
	105.0	49.	48.	46.	43.	40.	39.	36.	35.	34.	33.	33.
	95.0	85.	83.	80.	75.	71.	68.	64.	62.	60.	57.	59.
	90.0	126.	124.	117.	111.	105.	101.	95.	91.	87.	84.	84.
	87.5	160.	157.	149.	140.	132.	128.	121.	115.	109.	105.	105.
	85.0	207.	203.	192.	180.	170.	164.	153.	144.	138.	132.	133.
	82.5	267.	260.	246.	231.	218.	210.	196.	184.	174.	167.	169.
	80.0	337.	329.	309.	289.	273.	262.	244.	229.	217.	208.	210.
	77.5	416.	403.	379.	355.	332.	318.	296.	279.	265.	255.	256.
	75.0	491.	473.	441.	411.	385.	364.	342.	321.	308.	300.	300.
	72.5	534.	514.	479.	443.	410.	389.	364.	342.	330.	323.	323.
	70.0<<	526.	506.	472.	433.	400.	379.	352.	331.	318.	314.	311.
	67.5	473.	455.	426.	392.	365.	340.	315.	295.	281.	277.	275.
	65.0	405.	391.	366.	338.	314.	290.	269.	252.	239.	236.	233.
	62.5	342.	331.	310.	287.	267.	247.	229.	215.	206.	204.	201.
	60.0	296.	287.	269.	249.	231.	214.	200.	191.	184.	183.	183.
	57.5	266.	258.	241.	222.	207.	192.	180.	174.	170.	169.	169.
	55.0	246.	238.	222.	205.	190.	178.	166.	162.	159.	158.	158.
	52.5	232.	225.	210.	192.	178.	166.	156.	152.	151.	149.	149.
	50.0	221.	214.	199.	183.	169.	157.	148.	144.	143.	142.	140.
	47.5	212.	205.	191.	174.	160.	149.	140.	136.	135.	133.	133.
	45.0	204.	197.	183.	167.	153.	142.	133.	130.	128.	126.	126.
	42.5	196.	188.	174.	160.	146.	135.	126.	122.	119.	118.	118.
	40.0	187.	180.	166.	152.	139.	128.	119.	115.	111.	110.	110.
	37.5	177.	171.	158.	144.	132.	121.	112.	107.	103.	101.	101.
	35.0	166.	160.	148.	136.	124.	114.	104.	98.	95.	91.	91.
30.0	137.	132.	123.	114.	104.	96.	88.	81.	76.	73.	73.	
25.0	104.	101.	94.	88.	82.	75.	69.	64.	60.	59.	57.	
20.0	78.	76.	71.	67.	63.	59.	55.	52.	49.	48.	48.	
15.0	62.	60.	57.	54.	50.	48.	46.	43.	42.	41.	41.	
10.0	43.	42.	39.	36.	33.	30.	28.	26.	25.	23.	25.	
5.0	7.	7.	7.	6.	6.	5.	5.	4.	4.	4.	2.	
0.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB03691
ISSUE DATE: 08/30/17
PREPARED FOR: RAB LIGHTING INC. RC LIGHTING

PAGE: 9 OF 9

5-DEGREE ZONAL LUMEN SUMMARY

0- 5	0
5- 10	2
10- 15	6
15- 20	11
20- 25	19
25- 30	29
30- 35	43
35- 40	56
40- 45	70
45- 50	83
50- 55	99
55- 60	121
60- 65	166
65- 70	237
70- 75	271
75- 80	219
80- 85	144
85- 90	87
90- 95	55
95-100	39
100-105	29
105-110	22
110-115	17
115-120	13
120-125	9
125-130	7
130-135	5
135-140	3
140-145	2
145-150	1
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE ZONAL LUMEN SUMMARY

0- 10	2
0- 20	19
0- 30	67
0- 40	166
0- 50	319
0- 60	539
0- 70	942
0- 80	1432
0- 90	1663
0-100	1757
0-110	1808
0-120	1838
0-130	1854
0-140	1861
0-150	1864
0-160	1865
0-170	1865
0-180	1865