

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 1 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

LUMINAIRE: CAST FINNED METAL HOUSING, 6 CIRCUIT BOARDS EACH WITH 1 LED,
MOLDED PLASTIC REFLECTOR WITH SPECULAR FINISH AND 1 APERTURE PER LED,
CLEAR FLAT GLASS LENS IN CAST BROWN PAINTED METAL LENS FRAME.

LAMPS: SIX WHITE MULTI-CHIP LIGHT EMITTING DIODES (LEDs), 2 LEDs TILTED
63-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 75-DEGREES FROM
STRAIGHT AHEAD, 2 LEDs TILTED 67-DEGREES FROM VERTICAL BASE-UP POSITION
AND CANTED 68-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 58-DEGREES FROM
VERTICAL BASE-UP POSITION AND CANTED 40-DEGREES FROM STRAIGHT AHEAD.


ABSOLUTE: NOTE: THIS REPORT WAS PRORATED FROM RAB04367 WHICH WAS
ALED3T105Y/480. ACTUAL PERFORMANCE MAY VARY.

WATT: TOTAL INPUT WATTS = 109 W AT 480.0 VAC.

LED DRIVER: LED DRIVER: 2 x RD-H065-A1810-480

PROCEDURE: TEST PROCEDURE: IESNA LM-79-08

NOTE: LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE



Checked X.CAO

Approved D.WANG-MUNSON

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 2 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION


Values based on 25-foot mounting height

IES Classification: Short, Type III

Cutoff Classification (deprecated): Semicutoff

--- 1/2 Maximum Candela trace

× Maximum Candela point



REPORT NUMBER: PRORATED FROM RAB04367


PAGE: 3 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)


MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA



REPORT NUMBER: PRORATED FROM RAB04367
ISSUE DATE: 05/09/19
PREPARED FOR: RAB LIGHTING INC.
CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

PAGE: 4 OF 10

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 5 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

BUG Rating			B1 U0 G2		
Zonal Summary			Zone Ratings		
			B	U	G
Forward					
FL	(0° – 30°)	11858			
FM	(30° – 60°)	1191.9			
FH	(60° – 80°)	5551.0			
FVH	(80° – 90°)	4958.2			G2
		157.4			G2
Backward					
BL	(0° – 30°)	1199			
BM	(30° – 60°)	9.2			
BH	(60° – 80°)	289.6	B1		
BVH	(80° – 90°)	620.2	B1		
		284.2			G1
		5.0			G0
Upward					
UL	(90° – 100°)	0			
UH	(100° – 180°)	0.0		U0	
		0.0		U0	
Trapped Light					
Total Flux					
		0			
		13057			
		100.0			

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 6 OF 10


ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

Zonal Lumen Summary

(Linear scale)



REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 7 OF 10


ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)


Backlight Rating Details

(Logarithmic scale)




Uplight Rating Details

(Logarithmic scale)



Glare Rating Details

(Logarithmic scale)



REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 8 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

CANDELA TABULATION

	STREET	LATERAL ANGLE										
		SIDE	0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0	77.5
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	3.	3.	6.	6.	16.	17.	15.	13.	11.	11.	10.
	85.0	34.	31.	65.	92.	146.	138.	146.	182.	107.	78.	23.
V	82.5	114.	115.	296.	364.	572.	646.	623.	749.	481.	320.	100.
E	80.0	268.	304.	578.	888.	1316.	1937.	2229.	2280.	1257.	923.	373.
R	77.5	760.	774.	1174.	1792.	2372.	3298.	4156.	4340.	2659.	2098.	1173.
T	75.0	1510.	1497.	1893.	2502.	3148.	4169.	5545.	6254.	4700.	3882.	2520.
I	72.5	2040.	2011.	2476.	3194.	4064.	4963.	6546.	7701.	6338.	5676.	4145.
C	70.0	2489.	2397.	2950.	3823.	5043.	6816.	7195.	8062.	7375.	6970.	5046.
A	67.5	2904.	2789.	3478.	4628.	6443.	7682.	7740.	7671.	7476.	7322.	5488.
L	65.0	3485.	3463.	4414.	5592.	7234.	7504.	7798.	8061.	8246.	8248.	6197.
	62.5<<	4594.	4573.	5348.	6626.	7410.	7429.	7485.	7753.	8900.	8838.	6957.
A	60.0	5647.	5629.	6215.	6811.	7366.	7271.	6968.	7607.	8414.	8296.	6530.
N	57.5	5765.	5799.	5959.	6230.	6632.	6585.	6469.	7756.	7521.	7316.	5805.
G	55.0	5301.	5326.	5495.	5743.	5794.	6045.	6334.	7071.	6588.	6391.	4924.
L	52.5	4961.	4983.	5003.	5069.	5150.	5698.	6313.	6713.	5766.	5546.	4153.
E	50.0	4673.	4714.	4653.	4573.	4802.	5601.	5959.	6282.	5341.	5038.	3713.
	47.5	4373.	4358.	4333.	4331.	4686.	5331.	5274.	5453.	4839.	4503.	3360.
	45.0	4107.	4129.	4117.	4292.	4519.	4918.	5016.	4817.	4249.	3885.	2914.
	42.5	4062.	4086.	4164.	4421.	4378.	4631.	4657.	4334.	3746.	3471.	2622.
	40.0	3996.	4025.	4123.	4579.	4054.	4492.	4294.	4003.	3385.	3174.	2392.
	37.5	3952.	3950.	4114.	4348.	4189.	4349.	4024.	3916.	3152.	2974.	2238.
	35.0	4092.	4109.	4058.	4210.	4150.	4075.	3962.	3845.	3029.	2820.	2176.
	32.5	4286.	4260.	4009.	4046.	4044.	3816.	3809.	3755.	3083.	2861.	2144.
	30.0	4220.	4216.	3913.	3893.	3769.	3629.	3663.	3552.	2992.	2795.	2118.
	25.0	3986.	3999.	3612.	3451.	3421.	3443.	3335.	2974.	2494.	2339.	1854.
	20.0	3759.	3785.	3575.	3314.	3237.	3133.	2835.	2557.	2106.	2000.	1622.
	15.0	3342.	3375.	3269.	3020.	2796.	2591.	2394.	2175.	1814.	1739.	1483.
	10.0	2714.	2741.	2707.	2587.	2368.	2143.	1902.	1703.	1479.	1441.	1308.
	5.0	1958.	1970.	1928.	1885.	1799.	1728.	1626.	1514.	1408.	1382.	1320.
	0.0	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.

||
PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 9 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

CANDELA TABULATION

	HOUSE SIDE	LATERAL ANGLE										
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
V E R T I C A L A N G L E	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	10.	10.	9.	9.	9.	8.	7.	5.	4.	4.	4.
	85.0	13.	11.	11.	9.	8.	7.	6.	4.	4.	4.	4.
	82.5	32.	20.	15.	11.	8.	7.	6.	4.	4.	4.	4.
	80.0	157.	96.	50.	36.	9.	6.	5.	4.	4.	4.	4.
	77.5	622.	391.	128.	69.	11.	6.	5.	4.	4.	4.	5.
	75.0	1526.	648.	226.	87.	36.	9.	6.	5.	5.	6.	6.
	72.5	2392.	1007.	319.	141.	91.	29.	7.	5.	7.	7.	7.
	70.0	3074.	1417.	559.	234.	98.	35.	16.	5.	7.	7.	7.
	67.5	3205.	1510.	770.	329.	107.	47.	34.	8.	8.	8.	8.
	65.0	3535.	1478.	835.	389.	132.	83.	67.	20.	10.	10.	9.
	62.5<<	4089.	1826.	1033.	497.	172.	132.	79.	30.	15.	10.	9.
	60.0	4260.	2007.	1177.	547.	214.	168.	85.	37.	21.	14.	11.
	57.5	4057.	2054.	1201.	697.	249.	180.	93.	42.	22.	12.	11.
	55.0	3518.	1963.	1134.	741.	284.	188.	107.	51.	25.	11.	10.
	52.5	3029.	1935.	1084.	670.	328.	207.	116.	57.	32.	13.	10.
	50.0	2732.	1976.	1018.	671.	383.	232.	124.	61.	36.	40.	26.
	47.5	2464.	1882.	1026.	691.	461.	246.	143.	67.	41.	64.	74.
	45.0	2216.	1758.	1040.	696.	474.	277.	169.	74.	52.	46.	54.
	42.5	2032.	1631.	1039.	685.	510.	303.	184.	98.	58.	41.	41.
	40.0	1897.	1560.	1034.	668.	556.	332.	198.	119.	83.	71.	49.
37.5	1836.	1552.	1067.	662.	559.	353.	223.	128.	97.	85.	86.	
35.0	1847.	1600.	1133.	707.	551.	375.	260.	154.	106.	87.	80.	
32.5	1839.	1623.	1173.	742.	540.	429.	292.	183.	124.	97.	84.	
30.0	1782.	1572.	1191.	796.	542.	451.	309.	211.	157.	131.	115.	
25.0	1608.	1443.	1154.	902.	576.	415.	314.	231.	183.	181.	181.	
20.0	1433.	1300.	1046.	882.	684.	487.	358.	279.	242.	232.	217.	
15.0	1348.	1272.	1087.	936.	795.	655.	547.	498.	470.	477.	469.	
10.0	1231.	1175.	1064.	947.	872.	828.	795.	745.	689.	650.	650.	
5.0	1281.	1247.	1181.	1119.	1055.	1003.	962.	918.	888.	867.	866.	
0.0	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	1263.	

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04367

PAGE: 10 OF 10

ISSUE DATE: 05/09/19

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED3T105N/480 - RWLED3T105N/480 - RWLED3T105SFN/480 -
WPLED3T105N/480 (TYPE III)

5-DEGREE ZONAL LUMEN SUMMARY

0- 5	31
5- 10	101
10- 15	186
15- 20	281
20- 25	382
25- 30	500
30- 35	622
35- 40	725
40- 45	857
45- 50	1049
50- 55	1299
55- 60	1620
60- 65	1766
65- 70	1584
70- 75	1234
75- 80	659
80- 85	152
85- 90	10
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE ZONAL LUMEN SUMMARY

0- 10	133
0- 20	600
0- 30	1481
0- 40	2829
0- 50	4734
0- 60	7653
0- 70	11003
0- 80	12895
0- 90	13057
0-100	13057
0-110	13057
0-120	13057
0-130	13057
0-140	13057
0-150	13057
0-160	13057
0-170	13057
0-180	13057