

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 1 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

LUMINAIRE: CAST FINNED METAL HOUSING, 6 CIRCUIT BOARDS EACH WITH 1 LED,
MOLDED 2-PIECE PLASTIC REFLECTOR WITH SPECULAR FINISH AND 1 APERTURE PER
LED, CLEAR FLAT GLASS LENS IN CAST BROWN PAINTED METAL LENS FRAME.

LAMPS: SIX WHITE MULTI-CHIP LIGHT EMITTING DIODES (LEDs), 2 LEDs TILTED
56-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 18-DEGREES FROM
STRAIGHT AHEAD, 2 LEDs TILTED 57-DEGREES FROM VERTICAL BASE-UP POSITION
AND CANTED 16-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 57-DEGREES FROM
VERTICAL BASE-UP POSITION AND CANTED 22-DEGREES FROM STRAIGHT AHEAD.


ABSOLUTE: NOTE: THIS REPORT WAS PRORATED FROM RAB04361 WHICH WAS
ALED4T125Y/480. ACTUAL PERFORMANCE MAY VARY.

WATT: TOTAL INPUT WATTS = 108.0 W AT 480.0 VAC.

LED DRIVER: LED DRIVER: 2 x RDD-H65-36A-A1400-480

PROCEDURE: TEST PROCEDURE: IESNA LM-79-08

NOTE: LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE



Checked X.CAO

Approved D.WANG-MUNSON

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 2 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)


ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION
Values based on 25-foot mounting height

IES Classification: (does not classify)

Cutoff Classification (deprecated): Semicutoff

— — — — 1/2 Maximum Candela trace

× Maximum Candela point



REPORT NUMBER: PRORATED FROM RAB04361


PAGE: 3 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA



REPORT NUMBER: PRORATED FROM RAB04361


PAGE: 4 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



	LUMENS	PERCENT OF FIXTURE
DOWNWARD STREET SIDE	13552	96.5
DOWNWARD HOUSE SIDE	486	3.5
DOWNWARD TOTAL	14038	100.0
UPWARD STREET SIDE	0	0.0
UPWARD HOUSE SIDE	0	0.0
UPWARD TOTAL	0	0.0
TOTAL FLUX	14038	100.0

EFFICACY = 130.0 lm/W

ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 5 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

BUG Rating				B1	U0	G3
Zonal Summary		Lumens	% of Fixture	Zone Ratings		
				B	U	G
Forward		13552	96.5			
FL	(0° – 30°)	1698.1	12.1			
FM	(30° – 60°)	6632.6	47.2			
FH	(60° – 80°)	5094.2	36.3			G3
FVH	(80° – 90°)	127.4	0.9			G2
Backward		486	3.5			
BL	(0° – 30°)	263.8	1.9	B1		
BM	(30° – 60°)	174.0	1.2	B0		
BH	(60° – 80°)	41.8	0.3	B0		G0
BVH	(80° – 90°)	5.9	0.0			G0
Upward		0	0.0			
UL	(90° – 100°)	0.0	0.0		U0	
UH	(100° – 180°)	0.0	0.0		U0	
Trapped Light		0	0.0			
Total Flux		14038	100.0			

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 6 OF 10


ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

Zonal Lumen Summary

(Linear scale)



REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 7 OF 10


ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)


Backlight Rating Details

(Logarithmic scale)




Glare Rating Details

(Logarithmic scale)



Uplight Rating Details

(Logarithmic scale)



REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 8 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

CANDELA TABULATION

	STREET SIDE										
	0.0	2.5	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0	85.0
180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
87.5	16.	16.	14.	15.	12.	12.	15.	17.	17.	16.	17.
85.0	40.	38.	37.	82.	140.	104.	67.	55.	65.	28.	19.
V 82.5	145.	137.	123.	246.	423.	538.	475.	334.	215.	95.	35.
E 80.0	1413.	1360.	1272.	1601.	1862.	1686.	1361.	1270.	836.	399.	151.
R 77.5	3410.	3330.	3220.	3713.	3705.	3447.	2576.	2094.	1374.	685.	292.
T 75.0	5452.	5343.	5177.	5714.	5792.	5693.	4451.	2843.	1726.	913.	424.
I 72.5	7937.	7798.	7556.	8273.	8448.	7289.	5449.	3695.	2307.	1257.	619.
C 70.0	<10482.	10482.	10272.	9952.	9248.	7789.	5882.	4550.	3275.	2046.	962.
A 67.5	10049.	9843.	9682.	9536.	8966.	8240.	6361.	5046.	4031.	2719.	1424.
L 65.0	9725.	9612.	9369.	9636.	9092.	8479.	6636.	5434.	4362.	3237.	1713.
62.5	10130.	9943.	9575.	9741.	9169.	8814.	7312.	5507.	4406.	3476.	1744.
A 60.0	10237.	9919.	9453.	9398.	9222.	9142.	7969.	5945.	4347.	3418.	1614.
N 57.5	10019.	9665.	9136.	8899.	8757.	8124.	7812.	6396.	4382.	3202.	1545.
G 55.0	9207.	8934.	8488.	8256.	8036.	7571.	7769.	6466.	4421.	3022.	1582.
L 52.5	8606.	8454.	8114.	7847.	7762.	7353.	7221.	5972.	4320.	2896.	1571.
E 50.0	9122.	9000.	8770.	8534.	8115.	7104.	6894.	5617.	4210.	2940.	1626.
47.5	9752.	9642.	9351.	8570.	7950.	7435.	6352.	5236.	4078.	2966.	1626.
45.0	9342.	9287.	9081.	8375.	8125.	7243.	5879.	4860.	3948.	2873.	1700.
42.5	9240.	9212.	9099.	8638.	8000.	6581.	5578.	4692.	3865.	2789.	1808.
40.0	9210.	9165.	9052.	8510.	7303.	6232.	5399.	4683.	3840.	2741.	1858.
37.5	8520.	8467.	8367.	7790.	6807.	5960.	5255.	4607.	3836.	2836.	1904.
35.0	7957.	7910.	7791.	7169.	6432.	5706.	5180.	4522.	3731.	2861.	2022.
32.5	7370.	7337.	7239.	6638.	6097.	5484.	4989.	4440.	3637.	2812.	2094.
30.0	7001.	6970.	6887.	6244.	5869.	5305.	4793.	4266.	3607.	2806.	2173.
25.0	6420.	6410.	6354.	5806.	5401.	4956.	4495.	4017.	3498.	2836.	2285.
20.0	5782.	5780.	5753.	5459.	5054.	4648.	4242.	3797.	3252.	2772.	2258.
15.0	4990.	4980.	4964.	4812.	4533.	4191.	3855.	3458.	3074.	2786.	2298.
10.0	4140.	4125.	4142.	3992.	3837.	3579.	3345.	3136.	2930.	2648.	2287.
5.0	3190.	3203.	3194.	3159.	3098.	3019.	2933.	2787.	2624.	2453.	2251.
0.0	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.

||
PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 9 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

CANDELA TABULATION

HOUSE SIDE		LATERAL ANGLE									
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0 180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	17.	17.	16.	16.	15.	14.	12.	10.	8.	7. 7.
	85.0	18.	17.	16.	16.	14.	13.	11.	9.	7.	5. 5.
V	82.5	25.	21.	17.	16.	14.	12.	11.	8.	5.	3. 3.
E	80.0	60.	24.	19.	15.	13.	11.	10.	7.	4.	2. 2.
R	77.5	117.	40.	20.	16.	13.	11.	9.	7.	4.	2. 1.
T	75.0	219.	69.	20.	16.	13.	11.	9.	7.	3.	1. 0.
I	72.5	331.	103.	21.	17.	12.	11.	8.	6.	3.	1. 0.
C	70.0<<	525.	175.	24.	18.	15.	11.	8.	6.	3.	1. 0.
A	67.5	789.	233.	33.	18.	16.	11.	8.	6.	3.	1. 0.
L	65.0	956.	299.	44.	20.	16.	13.	8.	6.	3.	1. 0.
	62.5	964.	355.	51.	20.	16.	12.	11.	6.	3.	1. 0.
A	60.0	986.	430.	47.	38.	15.	13.	11.	9.	3.	1. 0.
N	57.5	1150.	487.	71.	41.	16.	13.	11.	11.	7.	5. 6.
G	55.0	1189.	568.	102.	37.	18.	15.	12.	11.	9.	8. 7.
L	52.5	1150.	638.	144.	35.	20.	15.	16.	12.	9.	9. 8.
E	50.0	1137.	630.	186.	39.	30.	16.	13.	18.	13.	10. 9.
	47.5	1126.	645.	215.	57.	38.	17.	13.	10.	8.	8. 8.
	45.0	1172.	716.	281.	63.	42.	22.	16.	9.	8.	7. 8.
	42.5	1292.	811.	343.	65.	43.	35.	16.	12.	8.	7. 8.
	40.0	1355.	895.	348.	97.	44.	41.	27.	17.	11.	9. 10.
	37.5	1407.	962.	392.	157.	41.	38.	46.	33.	19.	14. 16.
	35.0	1497.	1038.	445.	248.	47.	41.	55.	53.	38.	31. 33.
	32.5	1566.	1109.	515.	295.	64.	46.	47.	51.	51.	50. 55.
	30.0	1661.	1219.	635.	324.	142.	50.	43.	41.	45.	49. 56.
	25.0	1828.	1416.	874.	475.	336.	172.	57.	44.	42.	44. 46.
	20.0	1875.	1523.	1043.	688.	443.	322.	231.	149.	94.	81. 74.
	15.0	1999.	1699.	1344.	948.	689.	499.	414.	361.	319.	304. 299.
	10.0	2089.	1896.	1567.	1375.	1098.	929.	801.	710.	658.	648. 632.
	5.0	2154.	2057.	1895.	1756.	1630.	1555.	1490.	1446.	1385.	1333. 1350.
	0.0	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207.	2207. 2207.

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04361

PAGE: 10 OF 10

ISSUE DATE: 05/10/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED4T105N/480 - RWLED4T105N/480 - RWLED4T105SFN/480 -
WPLED4T105N/480 (TYPE IV)

5-DEGREE ZONAL LUMEN SUMMARY

0- 5	53
5- 10	157
10- 15	264
15- 20	376
20- 25	494
25- 30	617
30- 35	750
35- 40	912
40- 45	1077
45- 50	1221
50- 55	1328
55- 60	1518
60- 65	1623
65- 70	1586
70- 75	1288
75- 80	639
80- 85	124
85- 90	9
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE ZONAL LUMEN SUMMARY

0- 10	210
0- 20	851
0- 30	1962
0- 40	3625
0- 50	5923
0- 60	8768
0- 70	11978
0- 80	13904
0- 90	14038
0-100	14038
0-110	14038
0-120	14038
0-130	14038
0-140	14038
0-150	14038
0-160	14038
0-170	14038
0-180	14038