

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 1 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

LUMINAIRE: CAST FINNED METAL HOUSING, 6 CHIP ON BOARD LIGHT EMITTING DIODES, MOLDED PLASTIC REFLECTOR WITH SPECULAR FINISH, CLEAR GLASS LENS IN CAST BRONZE PAINTED METAL FRAME.

LAMPS: SIX WHITE MULTI-CHIP LIGHT EMITTING DIODES (LEDs), 2 LEDs TILTED 63-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 75-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 67-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 68-DEGREES FROM STRAIGHT AHEAD, 2 LEDs TILTED 58-DEGREES FROM VERTICAL BASE-UP POSITION AND CANTED 40-DEGREES FROM STRAIGHT AHEAD.


ABSOLUTE: NOTE: THIS REPORT WAS PRORATED FROM RAB04286 WHICH WAS ALED2T150Y. ACTUAL PERFORMANCE MAY VARY.

WATT: TOTAL INPUT WATTS = 159.0 W AT 120.0 VAC.

LED DRIVER: LED DRIVER: RDD-160

PROCEDURE: TEST PROCEDURE: IESNA LM-79-08

NOTE: LM-80 DATA AVAILABLE FROM MANUFACTURER FOR SOLID STATE SOURCE



Checked X.CAO

Approved D.WANG-MUNSON

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 2 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)


ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION
Values based on 25-foot mounting height

IES Classification: Medium, Type II

Cutoff Classification (deprecated): Semicutoff

--- 1/2 Maximum Candela trace

× Maximum Candela point



REPORT NUMBER: PRORATED FROM RAB04286


PAGE: 3 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA



REPORT NUMBER: PRORATED FROM RAB04286


PAGE: 4 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY. THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 5 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

BUG Rating			<div>B3</div> <div>U0</div> <div>G3</div>		
Zonal Summary			Zone Ratings		
			B	U	G
Forward					
FL	(0° – 30°)	15810			
FM	(30° – 60°)	1777.7			
FH	(60° – 80°)	7754.3			
FVH	(80° – 90°)	6170.1			G3
		107.7			G2
Backward					
BL	(0° – 30°)	3709			
BM	(30° – 60°)	1038.0	B3		
BH	(60° – 80°)	1767.5	B2		
BVH	(80° – 90°)	886.4	B2		G2
		17.1			G1
Upward					
UL	(90° – 100°)	0			
UH	(100° – 180°)	0.0		U0	
		0.0		U0	
Trapped Light					
Total Flux					
		0			
		19519			
		100.0			

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 6 OF 10


ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

Zonal Lumen Summary

(Linear scale)



REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 7 OF 10


ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)


Backlight Rating Details

(Logarithmic scale)




Glare Rating Details

(Logarithmic scale)



Uplight Rating Details

(Logarithmic scale)



REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 8 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

CANDELA TABULATION

	LATERAL ANGLE										
	STREET SIDE	0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0	80.0
											85.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	1.	1.	3.	6.	10.	12.	15.	35.	22.	18.
	85.0	4.	3.	8.	9.	14.	29.	98.	59.	66.	71.
V	82.5	11.	7.	15.	23.	94.	216.	428.	532.	615.	552.
E	80.0	23.	18.	79.	206.	353.	687.	1523.	2024.	2505.	2116.
R	77.5	43.	44.	267.	488.	896.	1789.	3362.	5511.	6722.	6402.
T	75.0	73.	138.	521.	991.	1824.	3030.	5049.	8617.	13005.	12632.
I	72.5	179.	332.	889.	1642.	2736.	4469.	7004.	9701.	16437.	17359.
C	70.0<<	417.	592.	1282.	2312.	3754.	5998.	8659.	10978.	16751.	17955.
A	67.5	805.	852.	1778.	3069.	4870.	7454.	9418.	12335.	14029.	15562.
L	65.0	1261.	1245.	2388.	3916.	6021.	8457.	10162.	12910.	13003.	12376.
	62.5	1680.	1743.	3012.	4770.	6778.	8869.	10436.	12910.	11912.	11048.
A	60.0	2058.	2261.	3552.	5255.	7217.	9059.	10772.	12444.	11520.	10672.
N	57.5	2385.	2692.	3831.	5608.	7258.	8959.	10942.	11478.	11072.	10677.
G	55.0	2812.	3034.	4026.	5623.	7279.	9072.	10790.	10954.	10462.	9810.
L	52.5	3241.	3382.	4118.	5841.	7472.	9271.	10298.	10342.	9256.	8449.
E	50.0	3710.	3755.	4411.	6086.	7757.	9146.	9913.	9531.	8314.	7627.
	47.5	4065.	4154.	4782.	6315.	7767.	8590.	9224.	8673.	7482.	6973.
	45.0	4346.	4466.	5063.	6347.	7532.	7994.	8049.	7890.	7076.	6514.
	42.5	4547.	4682.	5193.	6161.	6956.	7489.	7167.	7082.	6535.	6273.
	40.0	4631.	4721.	5183.	5719.	6492.	6887.	6859.	6543.	6157.	6059.
	37.5	4560.	4593.	5103.	5361.	5933.	6492.	6438.	6307.	5985.	5855.
	35.0	4419.	4413.	4726.	4881.	5484.	5913.	6115.	6217.	5682.	5474.
	32.5	4256.	4267.	4552.	4638.	5026.	5401.	5818.	5943.	5551.	5332.
	30.0	4135.	4203.	4497.	4543.	4883.	5080.	5446.	5460.	5213.	5159.
	25.0	3935.	3985.	4136.	4342.	4305.	4491.	4653.	4667.	4660.	4658.
	20.0	3765.	3769.	3879.	4165.	4208.	4239.	4123.	4201.	4236.	4152.
	15.0	3804.	3780.	3832.	3966.	4104.	4121.	4095.	4104.	3966.	3885.
	10.0	3709.	3709.	3739.	3757.	3848.	3926.	3968.	3960.	3928.	3885.
	5.0	3634.	3639.	3651.	3651.	3662.	3646.	3645.	3639.	3665.	3626.
	0.0	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.

||
PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 9 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

CANDELA TABULATION

HOUSE SIDE		LATERAL ANGLE										
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	12.	10.	11.	9.	8.	8.	7.	5.	4.	4.	4.
	85.0	33.	21.	15.	12.	11.	11.	9.	6.	5.	4.	4.
V	82.5	281.	120.	86.	29.	17.	13.	11.	13.	13.	12.	11.
E	80.0	1114.	602.	273.	100.	41.	14.	15.	17.	16.	13.	12.
R	77.5	3276.	1587.	266.	87.	40.	15.	15.	17.	16.	15.	13.
T	75.0	6826.	2660.	324.	130.	38.	25.	14.	16.	15.	14.	13.
I	72.5	10356.	3607.	1295.	325.	42.	30.	15.	15.	15.	13.	13.
C	70.0	12126.	4620.	1884.	513.	65.	30.	16.	18.	17.	13.	13.
A	67.5	11469.	5763.	2898.	665.	87.	34.	18.	18.	19.	14.	13.
L	65.0	9722.	5702.	3740.	803.	214.	48.	29.	22.	21.	17.	14.
	62.5	8537.	5750.	3158.	935.	521.	94.	40.	29.	25.	21.	17.
A	60.0	8136.	6010.	2971.	1191.	881.	136.	53.	50.	54.	31.	20.
N	57.5	7646.	5965.	2701.	1304.	1094.	291.	70.	59.	72.	36.	20.
G	55.0	7209.	5987.	2529.	1417.	1093.	478.	99.	69.	94.	36.	23.
L	52.5	6604.	5893.	2813.	1668.	1049.	603.	252.	85.	107.	35.	28.
E	50.0	5948.	5556.	2981.	1992.	1125.	625.	398.	176.	75.	42.	33.
	47.5	5823.	5382.	3060.	2074.	1148.	608.	484.	304.	166.	100.	78.
	45.0	5778.	5234.	3187.	2065.	1180.	692.	497.	396.	328.	180.	145.
	42.5	5651.	5075.	3386.	2108.	1224.	785.	480.	411.	363.	236.	193.
	40.0	5450.	4875.	3712.	2216.	1330.	862.	556.	395.	346.	248.	210.
	37.5	5256.	4771.	3975.	2340.	1489.	952.	672.	466.	309.	249.	219.
	35.0	4952.	4732.	3984.	2518.	1605.	1098.	755.	591.	374.	290.	261.
	32.5	4896.	4750.	4034.	2687.	1773.	1230.	861.	680.	473.	374.	340.
	30.0	4773.	4641.	3941.	2856.	1991.	1350.	970.	742.	535.	483.	454.
	25.0	4405.	4285.	3755.	3233.	2322.	1733.	1254.	935.	758.	704.	682.
	20.0	4021.	3973.	3594.	3182.	2728.	2182.	1780.	1426.	1226.	1166.	1123.
	15.0	3787.	3778.	3587.	3345.	3115.	2855.	2506.	2157.	1987.	1971.	1912.
	10.0	3811.	3802.	3673.	3530.	3340.	3162.	2974.	2808.	2730.	2649.	2625.
	5.0	3565.	3549.	3506.	3477.	3434.	3355.	3302.	3288.	3245.	3226.	3195.
	0.0	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.	3544.

CONE OF MAXIMUM CANDELA

REPORT NUMBER: PRORATED FROM RAB04286

PAGE: 10 OF 10

ISSUE DATE: 05/8/18

PREPARED FOR: RAB LIGHTING INC.

CATALOG NUMBER: ALED2T150N - RWLED2T150N - RWLED2T150SFN - WPLED2T150N (TYPE II)

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	84
5- 10	251
10- 15	412
15- 20	543
20- 25	679
25- 30	846
30- 35	1034
35- 40	1241
40- 45	1472
45- 50	1719
50- 55	1934
55- 60	2122
60- 65	2208
65- 70	2216
70- 75	1824
75- 80	808
80- 85	119
85- 90	6
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	335
0- 20	1290
0- 30	2816
0- 40	5091
0- 50	8282
0- 60	12338
0- 70	16762
0- 80	19394
0- 90	19519
0-100	19519
0-110	19519
0-120	19519
0-130	19519
0-140	19519
0-150	19519
0-160	19519
0-170	19519
0-180	19519