

# Photometric Test Report

## Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2014

## Prepared For

**RAB Lighting Inc.**

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, gary.xiao@rabweb.com

## Prepared By

**Deliver Co., Ltd.**

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

## Project Number

**DLF1812112**

## Data Number

**DLF1812112-8a**

## Test Date

**2018/12/14**

## Issue Date


**2018/12/15**

## Prepared By



Wangzun Zhu

## Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

## 1.0 Test Summary

DLC Technical Requirements v4.4

Outdoor - Mid Output Parking Garage Luminaire			
Requirement Category	Test Method	Requirements	Test value
Lamp Output (lm)	IES LM-79-2008	5000	5495
Minimum Luminaire Efficacy (lm/W)	IES LM-79-2008	90	116.5
Zonal Lumen Requirement (60°-80°)	IES LM-79-2008	≥30%	34.50%
Zonal Lumen Requirement (70°-80°)	IES LM-79-2008	≤25%	14.32%
Power (Input Wattage)	IES LM-79-2008	Worst Case	47.2
Input Voltage	IES LM-79-2008	Worst Case	480
Input Current	IES LM-79-2008	Worst Case	0.100
Allowable CCTs* (K)	IES LM-79-2008	≤5700	3066
Minimum CRI	IES LM-79-2008 CIE 13.3-1995	≥65	71
Power Factor	ANSI C82.77:2014	0.873	0.982
Total Harmonic Distortion (A%)	ANSI C82.77:2014	25.00%	18.74%

## 2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2018/12/14	IVGT5CU-50L730W4	H1
2	Goniophotometer Test	2018/12/14	IVGT5CU-50L730W4	H1
3	THD and PF Test	2018/12/14	IVGT5CU-50L730W4	H1

### Remark(If any)


- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

### 3.0 Production Description

**Luminaire Description:** IVGT5CU-50L730W4

**Electrical Specification:** 480V,50/60HZ, 50W

#### Photos of Luminaire Characteristics



## 4.0 LM-79 Measurement and Test Results

### 4.1 Integrating Sphere Test

Model No.	IVGT5CU-50L730W4	Sample ID.	H1
Operate time (Min.)	90	Stabilization time (Min.)	45

#### Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ .

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within  $\pm 0.2$  percent under load.

The sample was measured using  $4\pi$  geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

#### Test Conditions

Temperature ( $^{\circ}\text{C}$ )	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
25.3	480.03	60	0.101	47.6	0.982


#### Test Result

CCT (K)	CRI (Ra)	Duv
3066	71.3	2.1E-04

## 4.1 Integrating Sphere Test

### Spectroradiometric Parameters

#### Results




#### Spectral values

DominantWavelength	582.62 nm
Purity	0.503
PeakWavelength	582.86 nm
Width50%:	102.97 nm

#### Color Coordinates

Correlated Color Temperature		3066 K	
x: 0.4320	u: 0.2484	u': 0.2484	
y: 0.4018	v: 0.3465	v': 0.5197	
CRI01	67.5	CRI09	-41.0
CRI02	84.4	CRI10	65.1
CRI03	93.4	CRI11	60.8
CRI04	65.3	CRI12	53.5
CRI05	67.4	CRI13	71.2
CRI06	78.9	CRI14	96.7
CRI07	74.9	CRI15	58.3
CRI08	39.0	CRI16	55.8
ResultsCRI	71.3		



PlanckDistance 2.1E-004

## 4.0 LM-79 Measurement and Test Results

### 4.3 Goniophotometer Test

Model No.	IVGT5CU-50L730W4	Sample ID.	H1
Operate time (Min.)	90	Stabilization time (Min.)	45

#### Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ , measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within  $\pm 0.2$  percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at  $0.5^{\circ}$  vertical intervals and  $10^{\circ}$  horizontal intervals.

#### Test Conditions


Temperature ( $^{\circ}\text{C}$ )	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Orientation
25.1	479.99	60	0.100	47.2	0.981	Light Down

#### Test Result


Flux (lm)	Zonal Lumen Requirement ( $60^{\circ}$ - $80^{\circ}$ )	Zonal Lumen Requirement ( $70^{\circ}$ - $80^{\circ}$ )	Field Angle( $10^{\circ}$ )		Beam Angle( $50^{\circ}$ )		Luminous Efficacy (lm/W)
			Horizontal Spread	Vertical Spread	Horizontal Spread	Vertical Spread	
5495	34.50%	14.32%	231.7	231.5	161.8	160.9	116.5

### 4.3 Goniophotometer Test

#### Light Distrubtion Curve



#### Isolux Plot



### 4.3 Goniophotometer Test

#### Zonal Lumen Summary

DEG	LUMINOUS INTENSITY:cd									
$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315		
10	842.2	839.2	842.5	849.3	856.1	857.9	854.3	848.1		
20	836.4	828.8	836.8	855.3	869.1	871.8	861.4	848.1		
30	838.9	816.8	827.4	858.7	887.1	900.9	884.8	864.4		
40	940.0	888.0	884.5	928.2	979.4	1010	999.7	982.4		
50	1080	1019	1006	1069	1118	1148	1139	1132		
60	1183	1175	1111	1192	1215	1224	1204	1219		
70	963.3	1044	982.7	1070	1026	973.7	921.3	945.5		
80	446.3	534.5	521.5	583.0	510.1	438.2	374.4	390.4		
90	8.301	20.26	38.32	46.66	26.19	3.856	3.581	1.418		
100	17.85	21.84	20.68	17.78	13.40	27.99	29.37	32.61		
110	91.22	65.99	76.90	65.35	84.22	68.00	85.30	70.29		
120	65.10	66.62	72.38	55.84	69.29	56.02	62.78	56.44		
130	30.34	48.06	46.81	48.43	25.56	48.55	46.37	46.17		
140	40.45	35.34	31.83	35.15	39.85	35.32	35.42	33.10		
150	22.73	24.11	26.15	25.11	26.25	25.95	25.53	23.54		
160	18.08	19.30	20.74	19.17	18.28	19.75	22.08	18.61		
170	12.49	13.76	14.69	13.25	13.30	12.65	14.57	16.09		
180	12.56	12.06	11.66	11.81	12.27	12.00	11.10	11.31		



### 4.3 Goniophotometer Test

#### ZONAL LUMEN SUMMARY

	Zonal (lm)		Total (lm)	Percent
0-10	80.95	0 - 10	80.95	1.47%
10-20	240.94	0 - 20	321.89	5.86%
20-30	395.07	0 - 30	716.96	13.05%
30-40	564.63	0 - 40	1281.59	23.32%
40-50	791.64	0 - 50	2073.23	37.73%
50-60	1031.08	0 - 60	3104.31	56.49%
60-70	1108.55	0 - 70	4212.86	76.67%
70-80	787.09	0 - 80	4999.95	90.99%
80-90	239.11	0 - 90	5239.06	95.34%
90-100	15.53	0 - 100	5254.59	95.63%
100-110	53.48	0 - 110	5308.07	96.60%
110-120	75.63	0 - 120	5383.70	97.98%
120-130	45.04	0 - 130	5428.74	98.80%
130-140	31.05	0 - 140	5459.79	99.36%
140-150	18.69	0 - 150	5478.48	99.70%
150-160	10.23	0 - 160	5488.71	99.89%
160-170	4.97	0 - 170	5493.68	99.98%
170-180	1.18	0 - 180	5494.86	100.00%

### 3.2 Goniophotometer Test


#### COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

##### Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
Rw	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	103	103	103	98	98	98	95
1	104	98	92	87	101	95	90	85	90	86	82	85	82	78	81	78	75	73
2	92	82	73	66	89	79	71	65	75	68	62	71	65	60	67	62	58	55
3	82	69	59	51	79	67	58	50	63	55	49	60	53	47	56	51	46	43
4	74	60	49	41	71	58	48	40	55	46	39	51	44	38	49	42	37	34
5	67	52	41	34	64	50	41	33	48	39	32	45	37	32	43	36	31	28
6	61	46	36	28	59	45	35	28	42	34	27	40	32	27	38	31	26	23
7	56	41	31	24	54	40	30	24	38	29	23	36	28	23	34	27	22	20
8	52	37	27	21	50	36	27	21	34	26	20	32	25	20	31	24	19	17
9	48	34	24	18	47	33	24	18	31	23	18	30	23	17	28	22	17	15
10	45	31	22	16	44	30	22	16	29	21	16	27	20	15	26	20	15	13

#### CONE OF LIGHT DIAGRAM



## 5.0 THD and PF Test

Model No.	IVGT5CU-50L730W4	Sample ID.	H1
-----------	------------------	------------	----

### Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ . The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

### Test Results

Temperature (°C)	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
25.1	480.03	60	0.101	47.6	0.982	18.74%

## 6.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration	Calibration Due Date
DLF107	Integrating Sphere System	2017/12/28	2018/12/27
DLF108	Auxiliary Lamp	2017/12/28	2018/12/27
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-directional	2017/12/28	2018/12/27
DLF116	AC Power Source	2017/12/28	2018/12/27
DLF113	Power Meter	2017/12/28	2018/12/27
DLF112	Temperature Recorder	2017/12/28	2018/12/27
DLF114	Temperature & Humidity Datalogger	2017/12/28	2018/12/27
DLF101	Goniophotometer	2017/12/28	2018/12/27
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-directional	2017/12/28	2018/12/27
DLF104	AC Power Source	2017/12/28	2018/12/27
DLF507	DC Power Source	2017/12/28	2018/12/27
DLF102	Power Meter	2017/12/28	2018/12/27
DLF111	Temperature & Humidity Datalogger	2017/12/28	2018/12/27
DLF119	Power Meter	2017/12/28	2018/12/27
DLF031	Temperature data logger	2017/12/28	2018/12/27
DLF022	Digital power meter	2017/12/28	2018/12/27
DLF003	Temperature & Humidity Datalogger	2017/12/28	2018/12/27

\*\*\*\*\* End of Test Report\*\*\*\*\*