INSTRUCTIONS

H17 & H17XL ALUMINUM REFLECTOR INSTALLATION



RAB Lighting is committed to creating high-quality, affordable, well-designed and energy-efficient LED lighting and controls that make it easy for electricians to install and end users to save energy. We'd love to hear your comments. Please call the Marketing Department at 888-RAB-1000 or email: marketing@rablighting.com



IMPORTANT

READ CAREFULLY BEFORE INSTALLING FIXTURE. RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE.

RAB fixtures must be wired in accordance with the National Electrical Code and all applicable local codes. Proper grounding is required for safety. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

WARNING: Make certain power is OFF before installing or maintaining fixture. No user serviceable parts inside.


ALUMINUM REFLECTOR MOUNTING


- 1. Align the **Reflector** screw holes with the **Heat Sink** as shown in Fig. 1, and 2.
- 2. Install the Reflector onto the Heat Sink as shown in Fig. 3.
- 3. Secure the **Reflector** to the **Heat Sink** with (4) 4x8mm **Screws** (provided) as shown in Fig. 4.


CLEANING & MAINTENANCE

CAUTION: Be sure fixture temperature is cool enough to touch. Do not clean or maintain while fixture is energized.

- 1. Clean fixture and components with non-abrasive cleaning solution.
- 2. Do not open fixture to clean the LED. Do not touch the LED.







Note: These instructions do not cover all details or variations in equipment nor do they provide for every possible situation during installation operation or maintenance.

