

W22 Field-Adjustable, Ultra-Economy Wall Pack

PERFORMANCE:

W22-S-30	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
Optics	0°			0°			0°			0°		
Wattage	30W			25W			20W			15W		
Input Watts	30.9W	30.4W	30.9W	26.5W	26.1W	26.5W	22.7W	22.3W	22.7W	17.3W	17W	17.3W
Lumens	3,548	3,569	3,580	3,130	3,149	3,158	2,630	2,646	2,654	1,982	1,994	2,000
Lm/W	114.8	117.4	115.9	118.1	120.7	119.2	115.9	118.7	116.9	114.6	117.3	115.6
CRI	84	86	84	84	86	84	84	86	84	84	86	84
Voltage Ratings	480V											

W22-S-30	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
Optics	15°			15°			15°			15°		
Wattage	30W			25W			20W			15W		
Input Watts	31W	30.5W	31W	26.5W	26.1W	26.5W	22.7W	22.3W	22.7W	17.4W	17.1W	17.4W
Lumens	3,829	3,853	3,873	3,235	3,255	3,272	2,720	2,737	2,751	2,095	2,108	2,119
Lm/W	123.5	126.3	124.9	122.1	124.7	123.5	119.8	122.7	121.2	120.4	123.3	121.8
CRI	83	85	84	84	85	84	84	85	84	84	85	84
Voltage Ratings	480V											

W22-S-30	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
Optics	30°			30°			30°			30°		
Wattage	30W			25W			20W			15W		
Input Watts	31W	30.5W	31.0W	26.5W	26.1W	26.5W	22.7W	22.3W	22.7W	17.4W	17.1W	17.4W
Lumens	4,085	4,126	4,131	3,442	3,477	3,481	2,896	2,925	2,929	2,201	2,223	2,226
Lm/W	131.8	135.3	133.3	129.9	133.2	131.4	127.6	131.2	129.0	126.5	130.0	127.9
CRI	83	85	84	84	85	84	84	85	84	84	85	84
Voltage Ratings	480V											

W22-S-30	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
Optics	45°			45°			45°			45°		
Wattage	30W			25W			20W			15W		
Input Watts	31W	30.5W	31W	26.5W	26.1W	26.5W	22.7W	22.3W	22.7W	17.4W	17.1W	17.4W
Lumens	4,250	4,268	4,279	3,574	3,589	3,598	3,007	3,020	3,028	2,267	2,277	2,282
Lm/W	137.1	139.9	138.0	134.9	137.5	135.8	132.5	135.4	133.4	130.3	133.2	131.1
CRI	84	85	84	84	85	84	84	85	84	84	85	84
Voltage Ratings	480V											