

# X22 5-Way Selectable Floodlight



## PERFORMANCE

X22-320@ 320W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	318.8W	319W	318.8W	309.1W	309.3W	309.3W	320.7W	320.1W	319.8W
LUMENS	42,990	43,098	41,691	45,462	45,989	44,094	45,473	45,625	43,683
EFFICACY	134.8	135.1	130.8	147.1	148.7	142.6	141.8	142.5	136.6
CRI	82	82	82	83	83	83	83	82	83
VOLTAGE RATINGS	120-277V								

X22-320@ 320W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	312.3W	312.2W	312W	302.4W	302.6W	302.2W	313.4W	313.2W	313.2W
LUMENS	43,342	43,544	41,746	45,705	46,152	44,028	45,820	45,845	44,034
EFFICACY	138.8	139.5	133.8	151.1	152.5	145.7	146.2	146.4	140.6
CRI	82	82	82	84	83	83	83	83	82
VOLTAGE RATINGS	480V								

X22-320@ 280W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	279.9W	279.9W	280W	272.5W	272.5W	272.7W	282.7W	282W	282W
LUMENS	38,941	38,987	37,766	40,933	41,353	39,703	40,943	41,025	39,333
EFFICACY	139.1	139.3	134.9	150.2	151.8	145.6	144.8	145.5	139.5
CRI	82	82	82	83	83	83	83	82	83
VOLTAGE RATINGS	120-277V								

X22-320@ 280W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	271.3W	271.2W	271.2W	263.8W	263.9W	263.7W	273.3W	273.2W	273.3W
LUMENS	38,712	38,901	37,311	40,578	40,984	39,114	40,680	40,711	39,120
EFFICACY	142.7	143.4	137.6	153.8	155.3	148.3	148.8	149.0	143.1
CRI	82	82	82	84	83	83	83	83	82
VOLTAGE RATINGS	480V								

# X22 5-Way Selectable Floodlight



## PERFORMANCE

X22-320@ 240W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	239.8W	240.8W	239.9W	234.4W	235.3W	234.6W	243.2W	243.6W	242.6W
LUMENS	34,513	35,027	33,458	36,023	36,891	34,926	36,032	36,599	34,601
EFFICACY	143.9	145.5	139.5	153.7	156.8	148.9	148.2	150.2	142.6
CRI	83	82	82	83	83	83	83	82	83
VOLTAGE RATINGS	120-277V								

X22-320@ 240W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	232.4W	232.2W	232.2W	226.8W	226.9W	226.7W	235.1W	234.8W	235W
LUMENS	34,076	34,279	32,852	35,467	35,860	34,197	35,556	35,621	34,202
EFFICACY	146.6	147.6	141.5	156.4	158.0	150.8	151.2	151.7	145.5
CRI	83	82	82	84	83	83	83	83	82
VOLTAGE RATINGS	480V								

X22-320@ 200W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	203.6W	204.1W	203.8W	199.8W	200.3W	200.1W	207.3W	207.3W	206.9W
LUMENS	30,197	30,517	29,268	31,295	31,913	30,336	31,302	31,660	30,053
EFFICACY	148.3	149.5	143.6	156.6	159.3	151.6	151.0	152.7	145.3
CRI	83	83	83	83	83	83	83	82	83
VOLTAGE RATINGS	120-277V								

X22-320@ 200W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	197.1W	197.1W	197.1W	193.1W	193.3W	193.2W	200.2W	200.1W	200.2W
LUMENS	29,628	29,761	28,533	30,618	30,913	29,491	30,695	30,707	29,495
EFFICACY	150.3	151.0	144.8	158.6	159.9	152.6	153.3	153.5	147.3
CRI	83	83	83	84	83	83	83	83	82
VOLTAGE RATINGS	480V								