

# X22 5-Way Selectable Floodlight



## PERFORMANCE

| X22-500@ 500W   | 3000K    |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|----------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°      | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V  | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 495.5W   | 495.5W  | 494.1W  | 481.7W  | 479.5W  | 481.1W  | 496.2W  | 495.4W  | 495.9W  |
| LUMENS          | 69,392   | 69,306  | 65,359  | 74,093  | 72,901  | 69,793  | 73,110  | 72,570  | 68,920  |
| EFFICACY        | 140.0    | 139.9   | 132.3   | 153.8   | 152.0   | 145.1   | 147.3   | 146.5   | 139.0   |
| CRI             | 82       | 82      | 82      | 83      | 83      | 83      | 83      | 83      | 83      |
| VOLTAGE RATINGS | 120-277V |         |         |         |         |         |         |         |         |

| X22-500@ 500W   | 3000K   |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 491.8W  | 492.5W  | 491.5W  | 476.5W  | 476.8W  | 476.5W  | 493.6W  | 493.3W  | 493W    |
| LUMENS          | 70,106  | 70,133  | 66,240  | 74,455  | 74,100  | 70,402  | 74,374  | 73,514  | 69,848  |
| EFFICACY        | 142.5   | 142.4   | 134.8   | 156.3   | 155.4   | 147.7   | 150.7   | 149.0   | 141.7   |
| CRI             | 82      | 82      | 82      | 83      | 83      | 83      | 83      | 82      | 82      |
| VOLTAGE RATINGS | 480V    |         |         |         |         |         |         |         |         |

| X22-500@ 450W   | 3000K    |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|----------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°      | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V  | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 456.3W   | 455.4W  | 455.6W  | 445.4W  | 442.5W  | 445.4W  | 458.8W  | 457.1W  | 459.1W  |
| LUMENS          | 65,046   | 64,593  | 61,515  | 69,036  | 67,536  | 65,294  | 68,120  | 67,229  | 64,477  |
| EFFICACY        | 142.6    | 141.8   | 135.0   | 155.0   | 152.6   | 146.6   | 148.5   | 147.1   | 140.4   |
| CRI             | 82       | 82      | 82      | 83      | 83      | 83      | 83      | 83      | 83      |
| VOLTAGE RATINGS | 120-277V |         |         |         |         |         |         |         |         |

| X22-500@ 450W   | 3000K   |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 452.4W  | 453.1W  | 452.3W  | 440.1W  | 440.4W  | 440.3W  | 455.9W  | 455.7W  | 455.5W  |
| LUMENS          | 65,564  | 65,310  | 61,985  | 69,213  | 68,590  | 65,484  | 69,138  | 68,048  | 64,969  |
| EFFICACY        | 144.9   | 144.1   | 137.0   | 157.3   | 155.7   | 148.7   | 151.7   | 149.3   | 142.6   |
| CRI             | 82      | 82      | 82      | 83      | 83      | 83      | 83      | 82      | 82      |
| VOLTAGE RATINGS | 480V    |         |         |         |         |         |         |         |         |

# X22 5-Way Selectable Floodlight



## PERFORMANCE

| X22-500@ 420W   | 3000K    |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|----------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°      | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V  | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 418.4W   | 417.5W  | 418.2W  | 410W    | 407.3W  | 410.5W  | 422.3W  | 420.8W  | 423.1W  |
| LUMENS          | 60,873   | 60,437  | 57,706  | 64,152  | 62,746  | 60,820  | 63,301  | 62,461  | 60,059  |
| EFFICACY        | 145.5    | 144.8   | 138.0   | 156.5   | 154.1   | 148.2   | 149.9   | 148.4   | 141.9   |
| CRI             | 82       | 82      | 82      | 83      | 83      | 83      | 83      | 83      | 83      |
| VOLTAGE RATINGS | 120-277V |         |         |         |         |         |         |         |         |

| X22-500@ 420W   | 3000K   |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 414.3W  | 414.8W  | 414.2W  | 404.6W  | 404.8W  | 404.8W  | 419.1W  | 418.8W  | 418.8W  |
| LUMENS          | 61,158  | 60,847  | 57,832  | 64,108  | 63,453  | 60,667  | 64,038  | 62,951  | 60,189  |
| EFFICACY        | 147.6   | 146.7   | 139.6   | 158.4   | 156.8   | 149.9   | 152.8   | 150.3   | 143.7   |
| CRI             | 82      | 82      | 82      | 83      | 83      | 83      | 83      | 82      | 82      |
| VOLTAGE RATINGS | 480V    |         |         |         |         |         |         |         |         |

| X22-500@ 380W   | 3000K    |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|----------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°      | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V  | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 382.7W   | 381.6W  | 382.8W  | 376.5W  | 373.7W  | 377.2W  | 387.8W  | 386.1W  | 388.8W  |
| LUMENS          | 56,792   | 56,304  | 53,877  | 59,427  | 58,040  | 56,381  | 58,638  | 57,777  | 55,676  |
| EFFICACY        | 148.4    | 147.5   | 140.7   | 157.8   | 155.3   | 149.5   | 151.2   | 149.6   | 143.2   |
| CRI             | 82       | 83      | 83      | 83      | 83      | 83      | 83      | 83      | 83      |
| VOLTAGE RATINGS | 120-277V |         |         |         |         |         |         |         |         |

| X22-500@ 380W   | 3000K   |         |         | 4000K   |         |         | 5000K   |         |         |
|-----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| BEAM SETTING    | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     | 90°     | 75°     | 55°     |
| NEMA TYPE       | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V | 7H X 7V | 7H X 6V | 6H X 6V |
| INPUT WATTS     | 376.3W  | 376.5W  | 376.1W  | 369W    | 368.9W  | 369W    | 382.2W  | 381.6W  | 381.8W  |
| LUMENS          | 56,519  | 56,206  | 53,464  | 58,825  | 58,198  | 55,687  | 58,761  | 57,737  | 55,249  |
| EFFICACY        | 150.2   | 149.3   | 142.2   | 159.4   | 157.8   | 150.9   | 153.7   | 151.3   | 144.7   |
| CRI             | 82      | 83      | 83      | 83      | 83      | 83      | 83      | 82      | 82      |
| VOLTAGE RATINGS | 480V    |         |         |         |         |         |         |         |         |