

Multiple power packages.

GUS comes in two sizes (2 ft and 4 ft) and four power packages (50W, 36W, 25W and 18W)

50W 4 ft wrap 36W 4 ft wrap

25W 2 ft wrap

18W

2 ft wrap



100,000 HOUR LED LIFESPAN



0-10V







RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

Smooth light distribution.

High-reflectance finish and white diffusion lens softens light and reduces glare, unlike traditional prismatic lenses.




Joiner brackets

A joiner bracket accessory is available for side-entry or continuous-run mounting.




Designed to look good and safe to install.

Molded end caps and post-painted steel ensure rounded corners and smooth edges, making GUS safe to handle, while giving it a refined look.



Mounting options.

GUS can be surface mounted or mounted to a junction box. It can also be mounted in a variety of other ways, including chains, pendants and v-hooks (provided by others).





Ordering Matrix

Product Family GUS	Wattages/Size		Color Temp		Finish W		Driver /D10		Options	
	18 25 36 50	18W, 2 ft 25W, 2 ft 36W, 4 ft 50W, 4 ft	YN	5000K 4000K 3500K 3000K	W	White	/D10	120-277V, 0-10V Dimming	Blank /E2* /LC /LC/E2* /LCB	No Option Battery Backup Lightcloud® Controller Lightcloud® Controller w/ Battery Backup Lightcloud® Blue-enabled Lightcloud® Blue-enabled w/ Battery Backup