

RAB®

HAZPAN



Hazardous location lighting. HAZPAN—For Class 1 Div 2 applications.

Built tough.

Engineered for harsh-environment applications, the HAZPAN can withstand use in the presence of flammable vapor, gases, and ignitable dust/fibers. They're built for use in marine and hose-down environments, and ideal for manufacturing plants, chemical facilities, loading docks, and paper mills.

- Class I Division 2 (Groups A, B, C, D)
- Temperature rating of T5 or T6 (chain and ceiling mount)
- Certified to UL standard 1598 and 844





100,000-HOUR
LED LIFESPAN



5-YEAR
NO-COMPROMISE
WARRANTY

RAB's warranty is
subject to all terms
and conditions found at
rablighting.com/warranty


For low bay applications.

The HAZPAN is offered in 1x4, 2x4, and 2x2 models, each available in two wattages and a bright 5000K for maximized visibility. Battery backup is available for all three sizes.

40W or 60W



60W or 80W



40W or 60W



5000K

Secure installations, versatile mounting.

The HAZPAN comes standard with both suspension chains and ceiling mount brackets out of the box, with aircraft cable tethers included for additional support. A mounting kit is also available for recessed use in a ceiling or grid.

INCLUDED



CEILING MOUNT

INCLUDED



CHAIN MOUNT
(tethers included
for extra support)



RECESSED MOUNT KIT

[HAZPANRM1X4](#)
[HAZPANRM2X4](#)
[HAZPANRM2X2](#)

Microwave sensor control.

Available as a separate accessory, the HAZMVS is a microwave sensor engineered for hazardous location use. A second accessory kit is available with two mounting extensions.



HAZMVS



HAZMVS KIT

Ordering Matrix

Product Family	Size		Wattage	Color Temp		Finish		Mount	Voltage	Options
HAZPAN	1X4	1X4	40	40W (1x4 or 2x2)	Blank	5000K	Blank	Pendant / Ceiling Mount	Blank	No Options
	2X2	2X2	60	60W (all sizes)						MVS sensor (internal)
	2X4	2X4	80	80W (2x4 only)						Emergency Battery