



# PWLED



### FIELD ADJ.



ON/OFF



Super-thin, field-adjustable,  
and engineered for excellence.

PWLED—Transform your exterior lighting.





Big innovation,  
small package.

The lightweight PWLED was designed to cover large portrait wall pack footprints with a modern, ultra-thin fixture that helps reduce shipping and storage space/costs. The sleek housing maintains a minimal profile while providing powerful, efficient lighting—and it looks great doing it!

## Selectability in the field.

The PWLED's field-adjustable wattage delivers an impressive range of 1,950 to 9,500 lumens and it also boasts selectable CCT and an on/off photocell, letting you completely customize your lighting environment.





PWLED  
FEATURE PAGE



100,000-HOUR  
LED LIFESPAN



120-277V



480V



0-10V



COMPLIANT



PREMIUM



10  
YEAR  
NO-COMPROMISE  
WARRANTY

RAB's warranty is  
subject to all terms  
and conditions found at  
[rabilighting.com/warranty](http://rabilighting.com/warranty)

## Built for the long haul.

- A** Integrated dusk-to-dawn photocell
- B** Louvered reflector reduces glare
- C** Textured glass lens maximizes light output
- D** Sliding front design for simple installs
- E** Durable, powder-coated finish
- F** UL wet for challenging environments
- G** Operating temperature: -40°F to 113°F



## Versatile application.

Designed for 120-277V systems (480V option available), the PWLED adapts seamlessly to diverse environments. From commercial buildings and industrial facilities to educational institutions and retail establishments, this versatile fixture delivers reliable illumination for parking structures, security lighting, walkways, and corridors.

## Ordering Matrix

Family	Wattage	Mounting	Color Temperature	Finish	Driver	Controls
PWLED	Blank 72/41/13W	Blank Wall Mount	Blank 3000/4000/5000K CCT Adjustable	Blank Bronze	Blank /480 120-277V, 0-10V Dimming 480V, 0-10V Dimming	Blank Selectable On/Off Photocell