



Easy to make a dumb circuit smart for wireless control. XDIM makes updating to wireless a breeze.

## 0-10V Dimming.

The 0-10V models can easily manage a connected load up to 1,200W @ 120V or 1,385W @ 277V, with or without a passive infrared sensor for motion and daylight sensing. Ideal for new construction and retrofit applications where an existing 0-10V dimming circuit already exists.



## Maximum compatibility.

Gone are the days of having to purchase separate TRIAC or ELV dimmers. The XDIM lets you set it to either phase or, if you aren't sure, let it automatically detect for you! Adjust the low-end trim in the mobile app for the ultimate flexibility and compatibility.





FEATURE PAGE



3-YEAR LIMITED WARRANTY

RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty)

## Neutral is optional.

The XDIM phase-cut dimmers can be installed without a neutral for basic control. Add the neutral wire to allow for power monitoring of your lighting.



## 3-way in a new way.

The XDIM can be wired for either single pole or 3-way dimming—one dimmer does it all—and Lightcloud Blue models don't even require a 3-way traveler wire!



## Sensing options.

The XDIM phase dimmer is available with a passive infrared occupancy sensor that can control individual or groups of lights. Occupancy and vacancy sensing both include adjustable sensitivity and timeouts.



## Does what no other dimmer can.

- Control Lightcloud Blue devices wirelessly? No problem.
- Control standard wired devices? You bet.
- Control both wired and wireless at the same time? Easy peasy.
- Both Lightcloud Blue XDIM models can tackle it all!



WIRELESS  
*\*Neutral required*



WIRED  
*\*Neutral optional for TRIAC/ELV required for 0-10V*



WIRED + WIRELESS  
*\*Neutral required*

[Learn more about Lightcloud Blue](#)

## Ordering Matrix

Product Family	Finish	Voltage/Dimming	Options
XDIM	Blank B Black G Gray LA Light Almond	Matte White** Blank /D10	120V, Forward/Reverse Phase 120-277V, 0-10V*
			Blank /LCB /LCBS Standard Lightcloud Blue Lightcloud Blue w/PIR sensor

\* /D10 model only available with /LCB option  
\*\* Standard XDIM only available in matte white