


RAB®



A great, new, low-profile design with all the fixings!
Upgrade your area lighting with A34.

Super-low profile, super-high efficacy.

The A34 area light is built to impress! Its sleek, contemporary, low-profile design delivers on looks while its incredible efficacy outperforms the competition.

188
lm/W





RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

All the basics are covered.

Available in 4 lumen packages and 3 distributions (Types III, IV, and V) the A34 offers field-selectable wattage and CCT. Select from a universal pole mount, slipfitter, or wall mount to light various site applications with the same, great-looking fixture.



UNIVERSAL POLE MOUNT



WALL MOUNT



SLIPFITTER



Extra Large (340/270/220W)
Large (250/200/150W)




Medium (150/125/100W)



Small (100/80/50W)

The element of control.

All A34 models come standard with an on/off photocell and are available with an optional passive infrared or microwave motion sensor. For more fine-tuned control, both sensors are also offered with Lightcloud Blue compatibility and can quickly integrate with our powerful lighting control system.



Accessories.

House side shields are available for all models to eliminate light trespass and efficiently direct light only where it's needed.



A34S-HSS



A34M-HSS



A34L-XL-HSS

Turtle-friendly lighting.

For coastal areas that need to minimize the risk of disruption to wildlife, A34 is available in amber light models that are certified by both DarkSky and DLC LUNA.



*Commercial (S, M, L), Pedestrian (S, M), and Wildlife (S).

Ordering Matrix

Product Family	Distribution Type	Size/Wattage	Mounting	Color Temperature	Finish	Driver	Option	
A34	T3 Type III S T4 Type IV M T5 Type V L XL	Small (100/80/50W) Medium (150/125/100W) Large (250/200/150W) Extra Large (340/270/220W)	BLANK SF WM	Universal Pole Mount Slipfitter Wall Mount	BLANK 3000/4000/5000K Adjustable	BLANK W Bronze White	BLANK /480 * 120-277V, 0-10V Dimming 480V, 0-10V Dimming	BLANK /PIR /MVS /LCBS /LCBS/MVS No Option Passive Infrared Sensor Microwave Motion Sensor Lightcloud Blue Enabled w/PIR Sensor Lightcloud Blue Enabled w/MVS Sensor

* 480V available on M, L & XL models only

Product Family	Distribution Type	Size/Wattage	Mounting	Wavelength	Finish	Driver	
A34	T3 Type III S M L	Small (50W) Medium (100W) Large (150W)	BLANK SF WM	Universal Pole Mount Slipfitter* Wall Mount	YA Amber Wavelength 596 nm	BLANK W Bronze White	BLANK 120-277V, 0-10V Dimming

* A34 Amber is not LUNA/DarkSky certified for the SF version