



FEATURE PAGE



100,000-HOUR LED LIFESPAN









5-YEAR NO COMPROMISE WARRANTY

RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

## **Built Tough**



## Certified for:

- Class I Division 2 (Groups A, B, C, D)
- Class II Division 1 (Groups E, F, G)
- Class II Division 2 (Groups F, G)
- Class III
- "Hands free" tether for safe, easy wiring
- Temperature rating of T4A
- Corrosion-resistant aluminum
- Resistant to shock and vibrations (3G)
- Available with clear lens, frosted lens, clear globe, frosted globe
- Wire guard included for additional protection

## Secure installations for all facility areas.

The HAZLED is available with four mounting options for use throughout an entire site:



Surface and Pendant Mount (Remove yoke for *pendant mount)* 



Ceiling Mount



Stanchion Mount



Wall Mount



Mounting Accessory (Purchased seperately)

## Ordering Matrix

Product Family	Wattage		Color Temp		Mount		Finish		Lens/Globe		Voltage	
HAZLED												
	30	30W	Blank	5000K	Blank	Surface/Pendant	Blank	Gray	CF	Clear Flat Lens	Blank	120-277V, 0-10V Dimming
	60	60W			C	Ceiling			FF	Frosted Flat Lens	/480	480V, 0-10V Dimming*
	80	80W			S	Stanchion			CG	Clear Globe		
	120	120W			WM	Wall Mount			FG	Frosted Globe		