

Economy Downlights - Quick Reference Guide




50K-Hour Lifespan		Size & Shape	Trim	Replacement ¹	Wattage	Lumens	CRI	Color Temp.	Light Dist.	Dimming ²	Voltage	Field Adjustable
Recessed Retrofit												
	4"	BAFFLE SMOOTH	65W	8W	800/700	80 / 90 CRI	●●●●	95°	TRIAC	⚡	120V	-
	4"	BAFFLE	65/50W	7W	700/600	80 / 90 CRI	●●●●	100°	TRIAC	⚡	120V	-
	4"	BAFFLE SMOOTH	65W	8W	700	90 CRI	●●●●	95°	TRIAC	⚡	120V	
	5/6"	BAFFLE SMOOTH	75/65W	8W	850/725		●●●●	95°				-
			85/75W	10.5W	1050/900	80 / 90 CRI	●●●●	95°	TRIAC	⚡	120V	-
			100W	14W	1400/1200		●●●●	95°				-
	5/6"	BAFFLE	85/75W	10W	1000/900	80 / 90 CRI	●●●●	110°	TRIAC	⚡	120V	-
	5/6"	SMOOTH	75/100W	10/14W	850/1200	90 CRI	●●●●	120°	TRIAC	⚡	120-277V	-
5/6"	BAFFLE SMOOTH	65/75W	8/10.5W	725/900	90 CRI	●●●●	95°	TRIAC	⚡	120V		
2" Downlight												
	2"	BAFFLE	50W	8W	650	90 CRI	●●●●	38°	TRIAC	⚡	120V	-
Gimbal Downlight												
	2"	SMOOTH	35W	5W	400	90 CRI	●●●●	38°	TRIAC	⚡	120V	-
	3"	SMOOTH	50W	8W	600	90 CRI	●●●●	38°	TRIAC	⚡	120V	-
	4"	SMOOTH	75W	14W	1050	90 CRI	●●●●	38°	TRIAC	⚡	120V	-
Edge-Lit Wafer												
	3"	SMOOTH	60W	8W	550	80 / 90 CRI	●●●●	120°	TRIAC	⚡	120V	-
	4"	SMOOTH	60W	9W	550	80 / 90 CRI	●●●●	120°	TRIAC	⚡	120V	-
	6"	SMOOTH	65W	12W	750		●●●●	120°				-
			100/75W	15/14W	1150/950	80 / 90 CRI	●●●●	120°	TRIAC	⚡	120V	-
	6/8"	BAFFLE SMOOTH	75/125W	12/24W	900/1900	90 CRI	●●●●	120°	0-10V	⚡	120-277V	-
	4/6"	BAFFLE SMOOTH	60/75W	9/12W	650/900	90 CRI	●●●●	120°	TRIAC	⚡	120V	

1. All wattage equivalencies (EQs) are to incandescent lamps except the Performance Downlights which are to pin-based CFLs.
 2. Assuming compatible dimmers, Triac dims down to ~5% and 0-10V down to ~10%.
 3. 90 CRI models only.
 4. 90 CRI Recessed Retrofit models only.
 5. Select models only.

Color Temperature: ● 2700K ● 3000K ● 3500K ● 4000K ● 5000K



Economy Downlights - Quick Reference Guide

50K-Hour Lifespan		Size & Shape	Trim	Replacement ¹	Wattage	Lumens	CRI	Color Temp.	Light Dist.	Dimming ²	Voltage	Field Adjustable
Disk												
	4"	-	65W	11W	700/660	80 / 90 CRI	●●●●	120°	TRIAC	120V	-	
	5/6"	-	65W	11W	800/660	80 / 90 CRI	●●●●	120°	TRIAC	120V	-	
		-	75W	15W	1000/950							
Edge-Lit Surface Mount												
	5.5" □	SMOOTH	60W	10W	600	80 CRI	●●●	120°	TRIAC	120V	-	
	7" □	SMOOTH	75W	15W	900	80 CRI	●●●	120°	TRIAC	120V	-	
	9" □	SMOOTH	100W	20W	1200	80 CRI	●●	120°	TRIAC	120V	-	
	5.5" □	SMOOTH	60W	10W	600	90 CRI	●●●	120°	TRIAC	120-277V	-	
	7" □	SMOOTH	75W	15W	900	90 CRI	●●●	120°	TRIAC	120-277V	-	
	□	SMOOTH	75W	15W	900	90 CRI	●●	120°	0-10V	120-277V	-	
	9" □	SMOOTH	100W	20W	1200	90 CRI	●●	120°	TRIAC	120-277V	-	
	9" □	SMOOTH	100W	20W	1200	90 CRI	●●	120°	0-10V	120-277V	-	
Performance Downlight												
	6"	SMOOTH	18W	12W	1050/900	80 / 90 CRI	●●●	90°	0-10V	120-277V	-	
			32W	18W	1700/1500							
	8"	SMOOTH	2x26W	24W	2300/2000	80 / 90 CRI	●●●	90°	0-10V	120-277V	-	
			2x42W	33W	3500/3000							
	6"	SMOOTH	13/18W	9/12W	700/900	90 CRI	●●●	85°	0-10V	120-277V	3 CCT + 2 LUMEN	
			26/32W	14/18W	1200/1500							
	6"	SMOOTH	18/26/32W	7/10/18W	700/1000/1500	90 CRI	●●●	120°	0-10V	120-277V	3 CCT + 3 LUMEN	
	8"		26/32/42 (2x26)	10/15/22W	1000/1500/2000							
9.5"	42(2x26)/57(2x32)/2x42		20/25/32W	2000/2500/3000								

1. All wattage equivalencies (EQs) are to incandescent lamps except the Performance Downlights which are to pin-based CFLs.
 2. Assuming compatible dimmers, Triac dims down to ~5% and 0-10V down to ~10%.
 3. 90 CRI models only.
 4. 90 CRI Recessed Retrofit models only.
 5. Select models only.

Color Temperature: ● 2700K ● 3000K ● 3500K ● 4000K

