

Economy Downlights - Quick Reference Guide

 50K-Hour Lifespan	Size & Shape	Trim	Replacement ¹	Wattage	Lumens	CRI	Color Temp.	Light Dist.	Dimming ²	Voltage	Field Adjustable

Recessed Retrofit

	4"	BAFFLE SMOOTH	65W	8W	800/700	80 CRI / 90 CRI		95°	TRIAC	120V	-
	4"	BAFFLE	65/50W	7W	700/600	80 CRI / 90 CRI		100°	TRIAC	120V	-
	4"	BAFFLE SMOOTH	65W	8W	700	90 CRI		95°	TRIAC	120V	
	5/6"	BAFFLE SMOOTH	75/65W	8W	850/725			95°			-
			85/75W	10.5W	1050/900	80 CRI / 90 CRI		95°	TRIAC	120V	-
			100W	14W	1400/1200			95°			-
	5/6"	BAFFLE	85/75W	10W	1000/900	80 CRI / 90 CRI		110°	TRIAC	120V	-
	5/6"	SMOOTH	75/100W	10/14W	850/1200	90 CRI		120°	TRIAC	120-277V	-
	5/6"	BAFFLE SMOOTH	65/75W	8/10.5W	725/900	90 CRI		95°	TRIAC	120V	

2" Downlight

	2"	BAFFLE	50W	8W	650	90 CRI		38°	TRIAC	120V	-
--	----	--------	-----	----	-----	--------	---	-----	-------	------	---

Gimbal Downlight

	2"	SMOOTH	35W	5W	400	90 CRI		38°	TRIAC	120V	-
	3"	SMOOTH	50W	8W	600	90 CRI		38°	TRIAC	120V	-
	4"	SMOOTH	75W	14W	1050	90 CRI		38°	TRIAC	120V	-

Edge-Lit Wafer

	3"	SMOOTH	60W	8W	550	80 CRI / 90 CRI		120°	TRIAC	120V	-
	4"	SMOOTH	60W	9W	550	80 CRI / 90 CRI		120°	TRIAC	120V	-
	6"	SMOOTH	65W	12W	750	80 CRI / 90 CRI		120°	TRIAC	120V	-
			100/75W	15/14W	1150/950			120°			-
	6/8"	BAFFLE SMOOTH	75/125W	12/24W	900/1900	90 CRI		120°	0-10V	120-277V	-
	4/6"	BAFFLE SMOOTH	60/75W	9/12W	650/900	90 CRI		120°	TRIAC	120V	

1. All wattage equivalencies (EQs) are to incandescent lamps except the Performance Downlights which are to pin-based CFLs.

2. Assuming compatible dimmers, Triac dims down to ~5% and 0-10V down to ~10%.

3. 90 CRI models only


4. 90 CRI Recessed Retrofit models only

5. Select models only

Color Temperature:  2700K  3000K  3500K  4000K  5000K



Economy Downlights - Quick Reference Guide

 50K-Hour Lifespan	Size & Shape	Trim	Replacement ¹	Wattage	Lumens	CRI	Color Temp.	Light Dist.	Dimming ²	Voltage	Field Adjustable

	4"	-	65W	11W	700/660	 / 		120°			-
	5/6"	-	65W	11W	800/660	 / 		120°			-
			75W	15W	1000/950			120°			-

Edge-Lit Surface Mount

	5.5" 	 SMOOTH	60W	10W	600			120°			-
	7" 	 SMOOTH	75W	15W	900			120°			-
	9" 	 SMOOTH	100W	20W	1200			120°			-
	5.5" 	 SMOOTH	60W	10W	600			120°			-
	7" 	 SMOOTH	75W	15W	900			120°			-
		 SMOOTH	75W	15W	900			120°			-
	9" 	 SMOOTH	100W	20W	1200			120°			-
		 SMOOTH	100W	20W	1200			120°			-

Performance Downlight

	6"	 SMOOTH	18W	12W	1050/900	 / 		90°			-
			32W	18W	1700/1500			90°			-
	8"	 SMOOTH	2x26W	24W	2300/2000	 / 		90°			-
			2x42W	33W	3500/3000			90°			-
	6"	 SMOOTH	13/18W	9/12W	700/900			85°			
			26/32W	14/18W	1200/1500			85°			
	6"	 SMOOTH	18/26/32W	7/10/18W	700/1000/1500			120°			
	8"		26/32/42 (2x26)	10/15/22W	1000/1500/2000			120°			
	9.5"		42(2x26)/57(2x32)/2x42	20/25/32W	2000/2500/3000			120°			

1. All wattage equivalencies (EQs) are to incandescent lamps except the Performance Downlights which are to pin-based CFLs.

2. Assuming compatible dimmers, Triac dims down to ~5% and 0-10V down to ~10%.

3. 90 CRI models only

4. 90 CRI Recessed Retrofit models only

5. Select models only

Color Temperature:  2700K  3000K  3500K  4000K

