

FIELD ADJ

# The SHARK is more powerful than ever! Selectable wattage and CCT maximize versatility.

## Now with field adjustability.

1

The SHARK is still available in 3 sizes but now includes three selectable wattages and color temperatures, giving you 9 SKUs in one great washdown!

#### 50W 40W 30W

25W 20W 15W



100W

80W

60W

20-64



#### Low maintenance

SHARK is ideal for tunnels, stairwells, and other hard-to-reach areas where revamping is difficult and costly.



### Versatile options.

All models come standard with surface-mount brackets and V-hooks for chain mounting. Accessory mounting kits are also available with tamperproof clips, or for angled surface or junction box mounting.



100k-hour LED lifespan














Please visit rablighting.com to ee which models have DLC or DLC Premium listing.





5-YEAR, NO COMPROMISE WARRANTY

RAB's Warranty is subject to all terms and conditions found at rablighting.com/warranty



Chain-mounted brackets (standard)



Surface mount (standard)



6ft cord comes standard on 8ft models. Available as an option on 4ft and 2ft models.





Durable, 5VA polycarbonate housing

## Mounting



Toolless entry



Tether connection for easy wiring



Diffuse polycarbonate lens



Junction Box Mounting Bracket JBSHARK-G2 (For 2' and 4' models: contains 2 brackets)

JBSHARK8-G2 (For 8' models: contains 2 brackets)



45° Angle, Surface-Mount Bracket ANGSHARK-G2 (For 2' and 4' models: contains 2 brackets)

ANGSHARK8-G2 (For 8' models: contains 4 brackets)



Tamperproof Kit TPKSHARK-G2 (For 2' and 4' models: contains 4 brackets)

TPKSHARK8-G2 (For 8' models; contains 8 brackets)



Sensor Remote Control MSR1 (For PIR and MVS sensor models)

# Ordering Matrix

Product Family	Size/Wattages		Mounting		olor Temperature	Finish		Voltage		Options	
SHARK											
	2	2' (25/20/15W)	Blank Metal Brad	et Bla	nk 3500/4000/5000K	Blank Wh	ite	Blank	120-277V	Blank	No option
	2M	2' (25/20/15W)	with ho	iks					0-10V Dimming	/E	Battery Backup
		Marine Listed						/480	480V	/LC	Lightcloud Controller
	4	4' (50/40/30W)							0-10V Dimming	/MVS	Microwave Occupancy Sensor
	4M	4' (50/40/30W)								/PIR	Passive Infrared Occupancy Sensor
		Marine List								/LCBS	Lightcloud Blue PIR Sensor
	8	8' (100/80/60W)								/LCBS	/MVS Lightcloud Blue MVS Sensor
	8M	8' (100/80/60W)								/MVS/	E Microwave Occupancy Sensor
		Marine Listed									/Battery Backup
										/PIR/E	Passive Infrared Occupancy Snesor
											/Battery Backup
										/LCBS	
											/Battery Backup

/LCBS/MVS/E Lightcloud Blue MVS Sensor /Battery Backup