

The Bullet® flood you love, now in LED.
Perfect for residential and commercial landscapes.



BULLET12

RAB®
LIGHTING
RABWEB.COM • 888-722-1000

BULLET12

- Available in single or dual head configurations
- Each equivalent to 75W PAR30
- Professional grade with adjustable heads
- Mount as a downlight or uplight on RAB Mighty Post or junction box
- Available in bronze, white, black and verde green
- Microprismatic diffusion lens for smooth and even light distribution that eliminates glare
- Integrated TRIAC and ELV dimming
- 5-Year warranty
- 100,000-Hour LED Lifespan

Specifications

UL Listing: Suitable for wet locations
Suitable for mounting within 1.2m (4 ft.) off the ground

LEDs: Multi-chip, high-output, long-life LEDs

Driver: Innovative integrated driver technology with 120V TRIAC and ELV dimming*

Lifespan: 100,000-Hour LED Lifespan based on IES LM-80 results and TM-21 calculation

SINGLE BULLET12:

Nominal Watts @120V	12W
Input Watts	11.2
Output Lumens**	1071
Lumens Per Watt**	95
Color Accuracy (CRI)**	85
Color Temperature (CCT)**	4000K

Thermal Management: Superior heat sinking with external Air-Flow fins

Housing: Die-cast aluminum housing, lens frame & mounting plate

Reflector: Semi-specular, vacuum-metalized polycarbonate

Lens: Microprismatic diffusion lens for smooth and even light distribution

Mounting: Heavy-duty mounting arm with "O" ring seal & stainless steel screws

Gaskets: High-temperature silicone gaskets

Finish: Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals.

Color Uniformity: RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.

Color Stability: RAB LEDs exceed industry standards for chromatic stability

Green Technology: Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

IESNA LM-79 & LM-80 Testing: RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24: BULLET12 complies with 2013 California Title 24 building and electrical codes as a residential outdoor lighting fixture with no additional hardware required and as a commercial outdoor non-pole-mounted fixture < 30 Watts when used with a photosensor control. Select catalog number PCS900 (120V) to order a photosensor.


BULLET2x12 complies with 2013 California Title 24 building and electrical codes as a residential outdoor lighting fixture with no additional hardware required and as a commercial outdoor non-pole-mounted fixture < 30 Watts when used with a photosensor control. Select catalog number PCS900 (120V) to order a photosensor.

* Visit rabweb.com for a complete list of compatible dimmers.

** Values shown for neutral temperature. Visit rabweb.com for cool and warm.

Dimensions & Weight

BULLET12
Weight: 1.5 kg.



Ordering Information

Product Family	Wattage	Color Temperature	Finish
BULLET	12 2X12	Blank N Y	A W B VG
	12W 24W	5000K 4000K 3000K	Bronze White Black Verde Green