


4" Round 7W



6" Round 11W

PROJECT: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_


PREPARED BY: \_\_\_\_\_



## KEY FEATURES

- Low-profile, **back-lit** design
- Durable **thermoplastic** housing with **frosted lens**
- **New construction** or **retrofit** applications
- Installs on standard junction boxes **DSK4 3 3/4" DSK6 3 3/4"/5"/6"**
- Suitable for **wet locations**
- Suitable for use in closets when installed in accordance with **NEC guidelines**
- **Dimmable** down to 5% on compatible dimmers
- **5-Year, Limited Warranty**

## Disk - Surface Mount / Retrofit Field Adjustable, 90CRI



## TECHNICAL SPECIFICATIONS

### CONSTRUCTION

**Housing Material**  
Plastic

**Housing Finish**  
White

**Base Type**  
E26 Socket with ideal connector and wire leads included

**Lens**  
Frosted convex plastic diffuser provides uniform light without hotspots

**Beam Angle**  
110°

**LEDs**  
Back-lit LED technology utilizes high performing LEDs with 90+ CRI and an R9 > 50

**Mounting**  
Mounts on 3/4" standard junction boxes.  
Does not mount on pancake-style junction boxes  
Fixture snaps into place on included mounting bracket  
E26 screw-base connector included

### COMPLIANCE

**Safety Listing**  
UL Classified, UL Recognized

**Environment/Fixture Rating**  
Wet Location

**T24 JA8 Compliant**  
Only 90CRI models can be used to conform with the requirements of California Title 24 Part 6

**T20 Compliant**  
California Title 20 certified LED Tier 2 Lamp

**Energy Star Compliant**  
Yes

**Lawful for Sale in California**  
Yes

**NEC Compliant**  
Suitable for use in closets when installed in accordance with NEC® Section 410.16 (A)(1) and 410.16 (C)(3)

**FCC**  
Complies with Part 15 of the FCC Rules.

**RoHS**  
Mercury and UV free. RoHS-compliant components.

### PERFORMANCE

**Lifespan**  
50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Dimmable**  
TRIAC and ELV dimming compatibility

## TECHNICAL SPECIFICATIONS (CONTINUED)

### ELECTRICAL

**THD**  
 ≤20%  
**Power Factor**  
 ≥0.9  
**Input Voltage**  
 120V  
**Operating Frequency**  
 50/60Hz  
**Operating Temperature**  
 -20°C to 40°C

Note: All values are typical (tolerance +/- 10%)

### OTHER

#### Warranty

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

RAB warranty is subject to all terms and conditions found at: [rablighting.com](http://rablighting.com)

## PERFORMANCE


### Disk Field-Adjustable, 90CRI

	7W -4" ROUND	11W 6" ROUND
LUMENS	650	1,000
INPUT WATTS	7W	11W
LM/W	92	90
CRI	90	90
EQUIVALENCY	65W INCANDESCENT	75W INCANDESCENT
CCT	4CCT Selectable -2700K, 3000K, 4000K, 5000K	

## DIMENSIONS


### 4" Round

Weight: 0.6 lb




### 6" Round

Weight: 0.6 lb




## ACCESSORIES INCLUDING MOUNTING HARDWARE


### Mounting Hardware:



4" Round



Mounting Hardware



7 5/16"

6" Round

## ORDERING MATRIX

### Disk Field Adjustable, 90CRI

Family	Size-Shape	Wattage	CRI	Color Temperature	Voltage Rating	Fixture Finish	Trim Finish
<b>DSK</b>			<b>9</b>	<b>FA</b>	<b>120</b>	<b>W</b>	<b>S</b>
	4R = 4" Round 6R = 6" Round	for 4" Round 7 = 7W  For 6" Round 11 = 11W	9 = 90 CRI	FA = Field Adjustable (2700K/3000K/4000K/5000K)	120 = 120V	W = White	S = Smooth