

1X4



2X2



2X4



Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz

(1x4)

25W: 0.22A @ 120V; 0.13A @ 208V, 0.11A @ 240V, 0.10A @ 277V

30W: 0.26A @ 120V; 0.15A @ 208V, 0.13A @ 240V, 0.12A @ 277V

40W: 0.33A @ 120V; 0.19A @ 208V, 0.17A @ 240V, 0.15A @ 277V

(2x2)

25W: 0.22A @ 120V; 0.13A @ 208V, 0.11A @ 240V, 0.10A @ 277V

30W: 0.25A @ 120V; 0.15A @ 208V, 0.13A @ 240V, 0.12A @ 277V

40W: 0.33A @ 120V; 0.19A @ 208V, 0.17A @ 240V, 0.15A @ 277V

(2x4)

30W: 0.26A @ 120V; 0.15A @ 208V, 0.13A @ 240V, 0.12A @ 277V

40W: 0.34A @ 120V; 0.20A @ 208V, 0.17A @ 240V, 0.15A @ 277V

50W: 0.42A @ 120V; 0.24A @ 208V, 0.21A @ 240V, 0.18A @ 277V

Project:

Type:

Prepared By:

Date:

Technical Specifications

UL Listing:

Suitable for dry, damp locations.

IC rated for direct contact with thermal insulation.

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

LEDs:

Long-life, high-efficacy, mid-power, surface-mount LEDs.

Lifespan:

75,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

Dimming:

Driver includes control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit.

Ambient Temperature:

Suitable for use up to 40°C (104°F)

Lens:

Frosted polystyrene.

Mounting:

Recessed, surface, or suspended.

Housing:

Lightweight aluminum housing

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Replacement:

Replaces up to (4) F32T8 or (4) F28T5

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy America Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.


Features

- Field-adjustable lumen output (3 discrete steps)
- White tunable (3 discrete color temperatures)
- Can be changed during and after installation
- Battery backup option offered
- Available with Lightcloud®
- 75,000-Hour LED lifespan




Dimensions and Weight





EZPAN® FA 1X4
Weight: 7.1 lbs.



EZPAN® FA 2X2
Weight: 7.1 lbs.



EXPAN® FA 2X4
Weight: 13.4 lbs.



Performance


	25W			30W			40W		
	3500K <i>(Warm Neutral)</i>	4000K <i>(Neutral)</i>	5000K <i>(Cool)</i>	3500K <i>(Warm Neutral)</i>	4000K <i>(Neutral)</i>	5000K <i>(Cool)</i>	3500K <i>(Warm Neutral)</i>	4000K <i>(Neutral)</i>	5000K <i>(Cool)</i>
1 x 4									
Input Watts	26	26	26	31	30	31	40	39	41
Lumens	3032	3059	2960	3541	3584	3495	4391	4569	4351
Efficacy (lm/W)	115	120	113	114	119	112	109	117	107
Color Accuracy (CRI)	79	81	81	79	81	81	79	81	81
2 x 2									
Input Watts	27	26	26	31	30	31	42	39	41
Lumens	3140	3276	3117	3618	3810	3600	4425	4802	4435
Efficacy (lm/W)	119	128	118	115	125	115	107	123	109
Color Accuracy (CRI)	79	81	81	79	81	81	79	81	81
2 x 4									
Input Watts	31	30	31	40	39	40	48	46	48
Lumens	3642	3745	3600	4609	4845	4578	5365	5630	5311
Efficacy (lm/W)	119	127	118	114	125	114	111	122	110
Color Accuracy (CRI)	79	82	81	79	81	81	79	81	81

A. Surface Mounting Kits

SMKEZPAN1X4 - 1x4 Surface Mount Kit

SMKEZPAN2X2 - 2x2 Surface Mount Kit

SMKEZPAN2X4 - 2x4 Surface Mount Kit




B. Pendant Mounting Kits

PMKEZPAN1X4 - 1x4 Pendant Mount Kit

PMKEZPAN2X2 - 2x2 Pendant Mount Kit

PMKEZPAN2X4 - 2x4 Pendant Mount Kit




C. Recessed Drywall Mounting Kits

RMKPANEL1X4 - 1x4 Recessed Mounting Kit

RMKPANEL2X2 - 2x2 Recessed Mounting Kit

RMKPANEL2X4 - 2x4 Recessed Mounting Kit



Ordering Matrix



Product Family	Size	Voltage	Options
EZPANFA	1X4 = 1' x 4' 2X2 = 2' x 2' 2X4 = 2' x 4'	/D10 0-10V Dimming	Blank /LC No Option /E2 Lightcloud Controller Battery Backup
SMKEZPAN	Surface Mount Kit		Size 1X4 = 1' x 4' 2X2 = 2' x 2' 2X4 = 2' x 4'
PMKEZPAN	Pendant Mount Kit		Size 1X4 = 1' x 4' 2X2 = 2' x 2' 2X4 = 2' x 4'
RMKPANEL	Recessed Mount Kit		Size 1X4 = 1' x 4' 2X2 = 2' x 2' 2X4 = 2' x 4'