



For more product data, see Family Spec Sheets on rablighting.com

# | Field-adjustable flexibility.

One fixture does the work of three with field-adjustable light output. 2x2 models can be set to 19/29/39W and 2x4 models can be set to 29/39/49W. Output can be changed before, during and after installation.



## See the difference.

Edge-lit technology creates direct and indirect light, and the high-reflectance finish maximizes output. The diffuse light guide provides uniform distribution and reduces glare.



# Stay in control.

For additional energy savings and utility rebates, all models are available with a factory-installed Lightcloud Controller or Sensor. A microwave standalone sensor is also available for occupancy and daylight sensing.



### Accessories

### Recessed Mounting Kits

RMKPANEL2X2 - 2x2 Kit (shown) RMKPANEL2X4 - 2x4 Kit



### Surface Mounting Kits

SMKPANEL2X2 - 2x2 Kit (shown) SMKPANEL2X4 - 2x4 Kit



### **Ordering Matrix**

Product Family	Size	CRI and CCT	Driver	Controls	Options
SWISHFA-EDGE	2X2 19/29/39W <sup>1</sup> 2X4 29/39/49W <sup>1</sup>	840 80 CRI, 4000K 835 80 CRI, 3500K	U 120-277V, 0-10V dimming	Blank No optior /MVS Occupancy senso /LC Lightcloud controlle /LCS Lightcloud senso	r <b>/E2</b> Battery backup

<sup>1</sup>29W is factory default for 2x2, 39W is factory default for 2x4