

Panels Comparison Chart

	T17™	T34™	EZPAN®	EZPAN® FA	EZPAN® HE
FEATURES					
Available Sizes	2x2 2x4	2x2 2x4	1x4 2x2 2x4	1x4 2x2 2x4	1x4 2x2 2x4
Input Power	40W 50W	30W 40W	17W 30W 40W 50W	20/30/40W (2x2, 1x4) or 30/40/50W (2x4) (all in one)	12W 23W 30W 46W
Lumens/Watt (Typical)	90 lm/W	115 lm/W	115 lm/W	120 lm/W	140 lm/W
Lumen Maintenance (L70)	30,000 hr	50,000 hr	60,000 hr	75,000 hr	100,000 hr
Ambient Operating Temperature	-20°C (-4°F) to 40°C (104°F)	-20°C (-4°F) to 40°C (104°F)	-30°C (-22°F) to 50°C (122°F)	-30°C (-22°F) to 50°C (122°F)	-30°C (-22°F) to 50°C (122°F)
CCT	4000K 5700K	4000K 5000K	3000K 3500K 4000K 5000K	3500K/4000K/5000K (all in one)	3000K 3500K 4000K 5000K
Dimming	none (on/off only)	0-10V	0-10V	0-10V	0-10V
Field Adjustable	—	—	—	✓	—
White Tuning	—	—	—	✓	—
Mounting					
Recessed (RMKPANEL)	✓	✓	✓	✓	✓
Surface (SMKEZPAN)	—	—	✓	✓	✓
Suspended (PMKEZPAN)	—	—	✓	✓	✓
Lightcloud®	—	✓	✓	✓	✓
Battery Backup	—	—	✓	✓	✓
Case Quantity	2x2 = 8 per case* 2x4 = 4 per case* <i>must order in case qty increments</i>	2x2 = 4 per case* 2x4 = 2 per case* <i>must order in case qty increments</i>	1 per case	1 per case	1 per case
DLC	—	Standard	Standard	Standard	Premium
Warranty	2 year limited	5 year limited	5 year, no compromise	5 year, no compromise	5 year, no compromise
Price	¢	¢¢	\$	\$\$	\$\$\$

*must order in case quantity increments (any /LC option is quantity 1 per case)